



Delock 3.5" Mobile Rack for 1 x 2.5" U.2 NVMe SSD or SATA / SAS HDD / SSD

Description


This solid metal mobile rack by Delock can be installed into a free **3.5" bay** of a PC.

U.2 SFF-8639 interface also suitable for SATA and SAS

A 2.5" **U.2 SSD** can be mounted in the tray and slid into the rack.

A SATA or SAS HDD or SSD can also be installed. Depending on which memory type is installed, the appropriate cable must be connected to the backside and connected to the system. This is possible because the SFF-8639 port allows the connection of a SAS 29 pin or SATA cable.

The **hot swap** function allows the exchange of the hard disk drive during operation.



The mobile rack is equipped with a **key lock** to prevent unauthorised access.



Specification

· Connectors:

internal:

1 x U.2 SFF-8639 female

external:

1 x U.2 SFF-8639 male

• Suitable for 2.5" U.2 / SATA / SAS HDD / SSD:

HDD height up to 15 mm

supports 5 V SATA / SAS HDD / SSD

supports 12 V SAS HDD / SSD

• Data transfer rate:

SATA up to 6 Gb/s

SAS up to 12 Gb/s

NVMe up to 32 Gb/s

- 1 x On / Off switch
- Key lock
- · Hot Swap

System requirements

- Linux Kernel 3.19 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC with one free 3.5" bay
- · A free U.2 port or
- A free SATA / SAS port

Package content

- 3.5" mobile rack
- 2.5" mobile rack inner tray
- 2 x keys
- 6 x rack screws
- · 4 x hard drive screws
- User manual

Item no. 47232

EAN: 4043619472321

Country of origin: China

Package: White Box







Images

















General	
Form factor:	3.5"
Suitable for data medium:	2.5"
	SSD or HDD
	height up to 15.0 mm
Interface	
External:	1 x U.2 SFF-8639 male
Internal:	1 x U.2 SFF-8639 female
Technical characteristics	
Data transfer rate:	up to 32 Gbps
Physical characteristics	
Housing material:	metal
Colour:	black