

Delock Adapter USB 2.0 Type-A to 1 x Serial RS-232 D-Sub 9 pin male with nuts

Description

This USB 2.0 Type-A to serial adapter by Delock provides an RS-232 port for meters, POS systems, printers, modems, IoT devices, etc. The USB cable can optionally be used as an extension.



80 cm

Specification

- Anschlüsse:
1 x USB 2.0 Typ-A Stecker >
1 x Seriell RS-232 DB9 Stecker mit Muttern
- Chipsatz: FTDI FT232RL
- Kompatibel mit USB 3.0, USB 2.0 und USB 1.1
- Signale: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Datentransferrate bis zu 921,6 Kbps
- Kabellänge inkl. Anschlüsse: ca. 80 cm
- Farbe: schwarz

System requirements

- Linux Kernel 5.8.0 or above
- Mac OS 11.4 or above
- Windows 8.1/8.1-64/10/10-64/11
- Windows Server 2016/Windows Server 2019
- PC or laptop with a free USB Type-A port

Package content

- USB 2.0 to 1 x serial adapter
- Adapter DB9 to DB25
- Driver CD
- User manual


Item no. 61506

EAN: 4043619615063

Country of origin: China

Package:

Images



| General | |
|-------------------------------|--|
| Function: | Plug & Play |
| Specification: | USB 2.0 |
| Supported operating system: | Linux Kernel 2.6 or above Mac OS 10.11 or above Windows 10 32-bit Windows 10 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows Server 2016 Windows Server 2019 Windows 11 |
| Protection: | ESD (Electrostatic Discharge) |
| Interface | |
| connector: | 1 x USB 2.0 Type-A male |
| Connector 2: | 1 x Serial RS-232 DB9 male |
| Technical characteristics | |
| Chipset: | FTDI 232R |
| Data transfer rate: | up to 921.6 Kbps |
| Data transmission: | asynchronous Bi-directional full duplex |
| UART: | USB to serial UART |
| Physical characteristics | |
| Cable length incl. connector: | 80 cm |
| Screw type: | #4-40 UNC |
| Colour: | black |