



Delock Adapter USB 2.0 Type-A > 2 x Serial DB9 RS-232

Description

The USB 2.0 to serial adapter by Delock enables you to connect 2 serial devices to a free USB port of your PC or laptop.



1,5 m

Specification

- Connectors:
- 1 x USB 2.0 Type-A male > 2 x serial RS-232 DB9 male
- Chipset: FTDI
- · Serial connector with screw
- Data transfer rate up to 460.8 Kb/s
- Supports remote wake-up and power management
- Cable length: ca. 1.4 m

System requirements

- Windows Vista/7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB 2.0 to 2 x serial adapter
- Driver CD
- User manual

Item no. 61886

EAN: 4043619618866

Country of origin: China


Package: Retail Box

Images













Function: Plug & Play Specification: RS-232 (EIA / TIA) USB 2.0 Supported operating system: Windows 10 32-bit Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 8.1 64-bit LED indicator: Power Interface Connector 1: 1 x USB 2.0 Type-A male Connector 2: 2 x Serial RS-232 DB9 male Technical characteristics Chipset: FTDI FT2232HL Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)	General	
Supported operating system: Windows 10 32-bit Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8 32-bit Windows 8 32-bit Windows 8.1 32-bit Windows 8.1 32-bit Windows 8.1 64-bit Ush windows 8.1 64-bit LED indicator: Power Interface Connector 1: 1 x USB 2.0 Type-A male Connector 2: 2 x Serial RS-232 DB9 male Technical characteristics Chipset: FTDI FT2232HL Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)	Function:	Plug & Play
Supported operating system: Windows 10 32-bit Windows 7 32-bit Windows 7 64-bit Windows 8 32-bit Windows 8 64-bit Windows 8 1.32-bit Windows 8.1 32-bit Windows 8.1 64-bit LED indicator: Power Interface Connector 1: 1 x USB 2.0 Type-A male Connector 2: 2 x Serial RS-232 DB9 male Technical characteristics Chipset: FTDI FT2232HL Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)	Specification:	RS-232 (EIA / TIA)
Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 8.1 64-bit LED indicator: Power Interface Connector 1: 1 x USB 2.0 Type-A male Connector 2: 2 x Serial RS-232 DB9 male Technical characteristics Chipset: FTDI FT2232HL Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)		USB 2.0
Windows 7 32-bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 32-bit Windows 8.1 64-bit Undows 8.1 64-bit LED indicator: Power Interface Connector 1: 1 x USB 2.0 Type-A male Connector 2: 2 x Serial RS-232 DB9 male Technical characteristics Chipset: FTDI FT2232HL Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)	Supported operating system:	Windows 10 32-bit
Windows 7 64-bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit LED indicator: Power Interface Connector 1: 1 x USB 2.0 Type-A male Connector 2: 2 x Serial RS-232 DB9 male Technical characteristics Chipset: FTDI FT2232HL Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)		Windows 10 64-bit
Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit LED indicator: Power Interface Connector 1: 1 x USB 2.0 Type-A male Connector 2: 2 x Serial RS-232 DB9 male Technical characteristics Chipset: FTDI FT2232HL Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)		Windows 7 32-bit
Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit LED indicator: Power Interface Connector 1: 1 x USB 2.0 Type-A male Connector 2: 2 x Serial RS-232 DB9 male Technical characteristics Chipset: FTDI FT2232HL Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)		Windows 7 64-bit
Windows 8.1 32-bit Windows 8.1 64-bit LED indicator: Power Interface Connector 1: 1 x USB 2.0 Type-A male Connector 2: 2 x Serial RS-232 DB9 male Technical characteristics Chipset: FTDI FT2232HL Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)		Windows 8 32-bit
Windows 8.1 64-bit LED indicator: Power Interface Connector 1: 1 x USB 2.0 Type-A male Connector 2: 2 x Serial RS-232 DB9 male Technical characteristics Chipset: FTDI FT2232HL Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)		Windows 8 64-bit
LED indicator: Power Interface Connector 1: 1 x USB 2.0 Type-A male Connector 2: 2 x Serial RS-232 DB9 male Technical characteristics Chipset: FTDI FT2232HL Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)		Windows 8.1 32-bit
Interface Connector 1: 1 x USB 2.0 Type-A male Connector 2: 2 x Serial RS-232 DB9 male Technical characteristics Chipset: FTDI FT2232HL Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)		Windows 8.1 64-bit
Connector 1: 1 x USB 2.0 Type-A male Connector 2: 2 x Serial RS-232 DB9 male Technical characteristics Chipset: FTDI FT2232HL Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)	LED indicator:	Power
Connector 2: 2 x Serial RS-232 DB9 male Technical characteristics Chipset: FTDI FT2232HL Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)	Interface	
Technical characteristics Chipset: FTDI FT2232HL Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)	Connector 1:	1 x USB 2.0 Type-A male
Chipset: FTDI FT2232HL Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)	Connector 2:	2 x Serial RS-232 DB9 male
Data transfer rate: 2 x 460.8 Kbps Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)	Technical characteristics	
Data transmission: asynchronous full duplex Voltage: USB Bus powered (no additional power supply required)	Chipset:	FTDI FT2232HL
full duplex Voltage: USB Bus powered (no additional power supply required)	Data transfer rate:	2 x 460.8 Kbps
Voltage: USB Bus powered (no additional power supply required)	Data transmission:	asynchronous
		full duplex
Divisional above stavistics	Voltage:	USB Bus powered (no additional power supply required)
Physical characteristics	Physical characteristics	
Housing colour: black	Housing colour:	black
Housing material: Plastic	Housing material:	Plastic
Cable colour: black	Cable colour:	black
Cable length incl. connector: 1.4 m	Cable length incl. connector:	1.4 m
Screw type: #4-40 UNC	Screw type:	#4-40 UNC