

Delock Converter SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) with USB Type-C™ male > 22 pin SATA 6 Gbps male incl. power supply

Description

This Delock converter can be connected via USB Type-C™ interface to a PC or laptop. Thus, different SATA devices with 22 pin SATA interface can be operated. The included power supply can be used for 3.5" SATA HDDs or optical drives.



Specification

- Connector:
 - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ male >
 - 1 x SATA 6 Gb/s 22 pin male
 - 1 x DC jack
- Chipset: Asmedia ASM1351
- For SATA HDD, SATA SSD, optical drive etc.
- Supports SATA 1.5 Gb/s, SATA 3 Gb/s and SATA 6 Gb/s
- Data transfer rate up to:
 - SuperSpeed USB 10 Gbps,
 - SuperSpeed USB 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- SATA 6 Gbps
- LED indicator
- Bootable
- Plug & Play
- Length incl. connector: ca. 24.5 cm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.5 A
- Output: 12 V / 1.8 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.1 mm
 - outside: ø ca. 5.5 mm
 - length: ca. 9.5 mm

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.6, Mac OS 10.12
- PC or laptop with a free USB Type-C™ port

Package content

- Converter USB Type-C™ - SATA 6 Gb/s
- External power supply
- User manual

Item no. 62715

EAN: 4043619627158

Country of origin: China

Package: Retail Box

Images



General	
Function:	Plug & Play bootable
Supported operating system:	Linux Kernel 3.19 or above Mac OS 10.11 or above Windows 10 32-bit Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit
LED indicator:	Activity
Interface	
Connector 1:	1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ male
Connector 2:	1 x SATA 6 Gb/s 22 pin plug
connector 3:	1 x DC jack
Technical characteristics	
Data transfer rate:	6 Gb/s
Physical characteristics	
Cable length:	15 cm
Colour:	black
Power supply	
Type:	Euro wall power supply
Input:	AC 100 - 240 V / 50 - 60 Hz / 0.5 A
Output:	12 V / 1.8 A
Connector:	DC male 5.5 mm x 2.1 mm
Cable length:	1.75 m