

Delock HDMI Tester for EDID information with OLED display

Description

This HDMI tester with OLED display by Delock is used to read the EDID data stored in the monitor. The OLED display shows the maximum resolution, the refresh rate, the HDCP status and the color depth of the connected device.



Specification

- Connectors:
 - 1 x HDMI-A 19 pin male
 - 1 x USB Type Micro-B female (5 V power supply)
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Double row OLED display
- Plastic housing
- Colour: black
- Dimensions incl. connector (LxWxH): ca. 70.5 x 22.0 x 11.0 mm

Item no. 63327

EAN: 4043619633272
 Country of origin: China
 Package: Retail Box

System requirements

- Power source with a free USB Type-A female port

Package content

- HDMI EDID Tester
- USB Type-A to Type Micro-B cable, length ca. 80 cm
- HDMI extension cable, length ca. 22 cm
- HDMI coupler
- User manual

Images



General	
Specification:	HDCP 1.4 HDCP 2.2
Interface	
connector:	1 x High Speed HDMI-A 19 pin male
Connector 1:	1 x USB 2.0 Type Micro-B female
Technical characteristics	
Maximum screen resolution:	3840 x 2160 @ 60 Hz
Physical characteristics	
Housing colour:	black
Housing material:	Plastic
Length:	70 mm
Width:	22 mm
Height:	11 mm