



# Delock USB Type-C™ Docking Station for 1 x U.2 SSD

#### Description

This Docking Station by Delock enables an external connection of one **U.2 SSD** through the USB interface.

### Supports SuperSpeed USB 10 Gbps

A maximum data transfer rate of up to **USB 3.2 Gen 2** - 10 Gbps can be reached.

## Good cooling

The bottom consists of a **stable metal plate with cooling fins**. These provide a passive cooling for the inserted memory.



#### **Specification**

- Connectors:
- 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
- 1 x U.2 SFF-8639 female
- 1 x DC jack
- Chipset: Asmedia ASM2362
- Function key: 1 x On / Off switch
- · Data transfer rate up to 10 Gbps
- LED indicator for power and access
- Supports S.M.A.R.T.
- Supports TRIM
- Supports UASP
- Plug & Play
- Bootable
- · Colour: black
- Dimensions (LxWxH): ca. 138 x 80 x 23 mm

#### Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 1.5 A
- Output: 12.0 V / 3.0 A
- Ground outside, plus inside
- · Dimensions:

inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 10 mm

## System requirements

- · Android 10.0 or above
- · Chrome OS
- Linux Kernel 5.11 or above
- Mac OS 11.2.3 or above
- Windows 8.1/8.1-64/10/10-64/11
- iPad Air (4th Generation) or above
- iPad Pro (3rd Generation) or above
- Surface Pro 7
- PC or laptop with a free USB Type-A port or
- Device with a free USB Type-C<sup>™</sup> port or with a free Thunderbolt<sup>™</sup> 3 port

## Package content

- · Docking station
- Cable USB-C™ male to USB-C™ male, length ca. 80 cm

#### Item no. 63368

EAN: 4043619633685

Country of origin: China

Package: Retail Box





- $\bullet$  Cable USB-CTM male to USB Type-A male, length ca. 80 cm
- External power supply 12.0 V / 3.0 A
- Screws
- User manual

## **Images**

















| General                     |                                                               |
|-----------------------------|---------------------------------------------------------------|
| Function:                   | Plug & Play                                                   |
|                             | bootable                                                      |
|                             | TRIM                                                          |
|                             | S.M.A.R.T.                                                    |
| Suitable for data medium:   | 2.5"                                                          |
| Supported operating system: | Android 10.0 or above                                         |
|                             | Chrome OS                                                     |
|                             | Surface Pro 7                                                 |
|                             | Windows 10 32-bit                                             |
|                             | Windows 10 64-bit                                             |
|                             | Windows 8.1 32-bit                                            |
|                             | Windows 8.1 64-bit                                            |
|                             | iPad Pro (3rd Generation) or above                            |
|                             | iPad Air (4th Generation) or above                            |
|                             | Mac OS 11.2.3 or above                                        |
|                             | Windows 11                                                    |
|                             | Linux Kernel 5.11 or above                                    |
| Interface                   |                                                               |
| External:                   | 1 x DC jack 5.5 mm x 2.1 mm                                   |
|                             | 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female |
| Internal:                   | 1 x U.2 SFF-8639 female                                       |
| Technical characteristics   |                                                               |
| Chipset:                    | Asmedia ASM2362                                               |
| Data transfer rate:         | 10 Gbps                                                       |
| Physical characteristics    |                                                               |
| Length:                     | 138 mm                                                        |
| Width:                      | 80 mm                                                         |
| Height:                     | 23 mm                                                         |