



# Delock S/PDIF TOSLINK Switch 1 In 3 Out with USB Powered

## Description

With this TOSLINK splitter by Delock up to three TOSLINK devices can be operated at the same time at one TOSLINK output.

### Supports HD audio formats

The splitter supports all popular **2.0** and **5.1** audio formats such as **LPCM**, **Dolby Digital**, **DTS Audio** and therefore offers a sound experience like in a cinema.

### High resolution sampling rate

The splitter offers a sampling rate of up to **24 bit** and **96**  $\mathbf{kHz}$ . This allows a loss-free playback of the sound in the High-Res audio range.

### High transmission distance

The splitter supports an output transmission distance of up to **40 m** via an optical TOSLINK cable with a signal loss of less than 0.2 dB / m.

### **USB** powered

The splitter does not require an additional external power supply, power will be supplied via the included USB cable.

### Specification

- Connectors:
- Input:
- 1 x TOSLINK female S/PDIF
- 1 x USB Type Mini-B female (5 V power supply)
- Output: 3 x TOSLINK female S/PDIF • Supported sample rates: 32 / 44.1 / 48 / 96 kHz
- Bit rate 16 24 Bit
- Baud rate: max. 16 Mbps
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- · Supports signal retiming
- On / Off switch
- · Power LED (blue)
- Plastic housing
- Colour: black
- Dimensions (LxWxH): ca. 61 x 54 x 20 mm
- Voltage: 5 V
- Surge Protection
- USB bus powered

### System requirements

- · Digital optical audio signal
- · A free USB Type-A female port

### Package content

- TOSLINK splitter
- USB Type-A to Type Mini-B cable, length ca. 75 cm
- User manual



ltem no. 63397

EAN: 4043619633975

Country of origin: China

Package: Retail Box





# Images Images

© 2021 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.





General	
Specification:	DTS Audio
	Dolby Digital
	LPCM
LED indicator:	Power
Interface	
Output:	3 x TOSLINK female S/PDIF
Input:	1 x TOSLINK female S/PDIF
	1 x USB Type Micro-B female (5 V power supply)
Technical characteristics	
Bit rate:	16 - 24 Bit
Data transfer rate:	max. 16 Mbps
Voltage:	USB bus powered
Sample rate:	32 / 44,1 / 48 / 96 kHz
Physical characteristics	
Housing colour:	black
Length:	61 mm
Width:	54 mm
Height:	20 mm
LED colour:	blue