

Delock USB Type-C™ 3.1 Docking Station for 1 x SATA HDD / SSD

Description

This Docking Station by Delock enables an external connection of one 2.5" or 3.5" SATA HDD or SSD through the USB-C™ interface. This solution does not require an external enclosure since the drive can just plug in directly into the docking station.



Specification

- Connectors:
 - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female
 - 1 x SATA 6 Gb/s 22 pin receptacle
 - 1 x DC jack
- Chipset: Asmedia ASM235CM
- Function key:
 - 1 x On / Off switch
- For 2.5" and 3.5" SATA HDD / SSD
- Suitable for all SATA HDDs up to SATA 6 Gb/s
- Data transfer rate up to 6 Gb/s
- LED indicator for power and access
- Dimensions (LxWxH): ca. 129 x 75 x 57 mm
- Plug & Play

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.8 A
- Output: 12 V / 2 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.1 mm
 - outside: ø ca. 5.5 mm
 - length: ca. 10 mm

System requirements

- Linux Kernel 4.9.4 or above
- Mac OS 10.13.3 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C™ port

Package content

- Docking station
- Cable USB-C™ male to USB-C™ male, length ca. 80 cm
- External power supply 12 V / 2 A
- User manual

Item no. 63958

EAN: 4043619639588

Country of origin: China

Package: • Retail Box



Images



General	
Function:	Plug & Play
Suitable for data medium:	2.5" 3.5" SSD or HDD
Supported operating system:	Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Mac OS 10.13.3 or above Linux Kernel 4.9.4 or above
Interface	
External:	1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female 1 x DC 12 V power connector
Internal:	1 x SATA 6 Gb/s 22 pin receptacle
Technical characteristics	
Chipset:	Asmedia ASM235
Physical characteristics	
Housing material:	Plastic
Length:	129 mm
Width:	75 mm
Height:	57 mm
Colour:	black