

# Delock Digital Audio Converter to Analogue HD with Headphone Amplifier

## Description

The digital audio converter (DAC) by Delock converts a digital audio signal into an analogue stereo signal. For example a DVD or Blu-ray player can be connected to the input of the device and the signal can be supplied via optical TOSLINK or via S/PDIF coaxial connection. At the output port, the audio signal is transmitted via the RCA connection. Additionally, a headphone jack and volume control are integrated.



## Specification

- Connectors:
  - Input:
    - 1 x TOSLINK female S/PDIF
    - 1 x Coaxial female S/PDIF
    - 1 x USB Type Micro-B female (5 V power supply)
  - Output:
    - 2 x RCA female
    - 1 x 3.5 mm 3 pin stereo jack female
- Frequency response: 20 Hz - 20 kHz +/- 0.2 dB
- Signal-to-noise ratio (SNR): ca. 105 dB
- Supported sample rates: 32 / 44.1 / 48 / 96 / 192 kHz
- Bit rate 16 - 24 Bit
- Volume control
- Output power: max. 0.3 W total
- Metal housing
- Colour: black
- Dimensions (LxWxH): ca. 70 x 60 x 20 mm

## System requirements

- Digital audio signal
- Power source with a free USB Type-A female port

## Package content

- Converter digital > analogue
- USB Type-A to Type Micro-B cable, length ca. 100 cm
- User manual

## Item no. 63972


EAN: 4043619639724

Country of origin: China

Package: • Retail Box



## Images



Interface	
Output:	1 x 3.5 mm 3 pin stereo jack female 2 x RCA female (red, white)
Input:	1 x TOSLINK female S/PDIF 1 x Coaxial female S/PDIF 1 x USB Type Micro-B female (5 V power supply)
Technical characteristics	
Sample rate:	24 Bit / 192 kHz
Physical characteristics	
Length:	70 mm
Width:	60 mm
Height:	20 mm