

Delock 3.5" USB 3.2 Gen 1 Front Panel 1 x USB Type-C™ + 2 x USB Type-A + SD and Micro SD slot

Description

This front panel by Delock can be installed into a free 3.5" bay of a computer. It has two USB 3.2 Gen 1 Type-A and one USB 3.2 Gen 1 Type-C port. It will be connected to the motherboard internally via a pin header male port.

Integrated Card Reader

In addition, the hub with integrated card reader expands the PC by an SD and a Micro SD slot.



Specification

- Connectors:
 - external:
 - 1 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) USB Type-C™ female
 - 2 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) Type-A female
 - 1 x SD slot
 - 1 x Micro SD slot
 - internal:
 - 1 x 19 pin USB pin header female port on the cable
 - 1 x SATA 15 pin power connector
- Chipset: VIA VL817, Genesys Logic GL3224
- Data transfer rate up to:
 - SuperSpeed 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- The Card Reader supports following memory cards:
 1. Slot Secure Digital
 - SD, SD3.0 UHS-I, SD High Capacity (SDHC), SD Ultra, SDHC Ultra, SDXC, MMC-I, MMC-II, MMC 4.0, Mini SD, Mini SDHC, MMCmobile, RS-MMC, RS-MMC 4.0
 2. Slot Micro Secure Digital
 - MicroSD, Micro SDHC, Micro SDHC Ultra, T-Flash, MMCmicro
- Cable data:
 - 1 x 19 pin USB pin header female cable, length ca. 54 cm (without connectors)
- 3.5" metal frame
- Colour: black
- Hot Swap, Plug & Play

System requirements

- Linux Kernel 3.3 or above
- Windows 8.1/8.1-64/10/10-64
- PC with one free 3.5" bay
- Motherboard with a free 19 pin USB pin header male
- Power supply with SATA 15 pin receptacle

Package content

- 3.5" front panel
- USB pin header female cable
- Screws
- User manual

Item no. 64058

EAN: 4043619640584

Country of origin: China

Package: Retail Box

Images



General	
Form factor:	3.5"
Function:	Hot Swap Plug & Play
Supported operating system:	Linux Kernel 3.3 or above Windows 10 64-bit Windows 8.1 64-bit
Interface	
External:	1 x Micro SD slot 1 x SD slot 1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ female 2 x SuperSpeed USB (USB 3.2 Gen 1) USB Typ-A Buchse
Internal:	1 x 19 pin USB 3.0 pin header female 1 x SATA 15 pin power connector
Technical characteristics	
Data transfer rate:	USB 3.2 Gen 1 up to 5 Gbps
Physical characteristics	
Housing material:	metal
Length:	102 mm
Width:	95 mm
Height:	26 mm
Colour:	black