

# Delock USB Type-C™ 3.2 Gen 2 to SATA Converter

## Description

This converter by Delock can be connected via USB Type-A interface to a PC or laptop. Thus a **2.5" or 3.5" SATA HDD or SSD** with a 22 pin SATA interface can be used.



## Specification

- Connectors:
  - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
  - 1 x SATA 6 Gb/s 22 pin receptacle
  - 1 x DC jack
- Chipset: VIA VL716
- For 2.5" and 3.5" SATA HDD / SSD
- Supports SATA 1.5 Gb/s, SATA 3 Gb/s and SATA 6 Gb/s
- Data transfer rate up to 6 Gb/s
- LED indicator
- Colour: black
- Dimensions (LxWxH): ca. 72 x 29 x 14 mm

## Power supply specification

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.8 A
- Output: 12 V / 2 A
- Ground outside, plus inside
- Dimensions:
  - inside: ø ca. 2.5 mm
  - outside: ø ca. 5.5 mm
  - length: ca. 10 mm

## System requirements

- Chrome OS 76.0 or above
- Linux Kernel 3.12 or above
- Mac OS 10.15.1 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

## Package content

- Converter
- Cable USB-C™ male to USB Type-A male, length ca. 1 m
- Power supply
- User manual

## Item no. 64104

EAN: 4043619641048

Country of origin: China

Package: • Retail Box

Images



**General**

Suitable for data medium:	2.5" 3.5"
Supported operating system:	Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 3.12 or above Chrome OS 76.0 or above Mac OS 10.15.1 or above

**Interface**

Connector 1:	1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
Connector 2:	1 x SATA 6 Gb/s 22 pin receptacle
connector 3:	1 x DC jack

**Technical characteristics**

Chipset:	VIA VL716
Data transfer rate:	6 Gb/s

**Physical characteristics**

Cable length:	1 m
---------------	-----