

# Dual HDMI Adapter with 4K 60 Hz and PD 3.0 for MacBook

## Description

This adapter by Delock can be connected to a MacBook with two adjacent Thunderbolt™ 3 ports, e.g. the MacBook Pro. **Two monitors** can be operated at the HDMI outputs with **4K 60 Hz simultaneously**.

### USB Power Delivery (USB PD 3.0) support up to 100 watt

The adapter has a USB Type-C™ Power Delivery port to connect the power supply of the laptop to charge it. The adapter can also be used without a power supply.

### Small sturdy helper

Due to its **small dimensions and its sturdy housing**, this Delock adapter is particularly suitable for travelling. It can simply be packed into the bag together with the laptop and used as needed.



## Note

Only one additional external monitor can be connected to MacBook devices with M1 chipset.

## Specification

- Connectors:
  - 2 x USB Type-C™ male
  - 2 x HDMI-A female
  - 1 x USB Type-C™ female (power supply)
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Transmission of audio and video signals
- Functions: Mirrored or Extended
- USB Power Delivery (PD) 3.0
- Metal housing
- Rubberized bottom
- Colour: grey
- Dimensions (LxWxH): ca. 62 x 40 x 11 mm

## System requirements

- MacBook Pro with two adjacent Thunderbolt™ 3 ports

## Package content

- Adapter
- User manual


## Item no. 64123

EAN: 4043619641239

Country of origin: China

Package: Retail Box

## Images



Interface	
Connector 1:	2 x USB Type-C™ male
Connector 2:	2 x HDMI-A female
connector 3:	1 x USB Type-C™ Power Delivery female
Technical characteristics	
Maximum screen resolution:	3840 x 2160 @ 60 Hz
Physical characteristics	
Housing material:	metal
Colour:	grey