

# Delock Adapter Sub-D 9 pin male to Terminal Block 10 pin with Enclosure

## Description

This terminal block adapter by Delock can be used to connect bare wires. Thus the adapter is not only convenient for special industry applications, but also for the hobby area, e.g. railway modelling.

### Protection by enclosure

The plastic enclosure protects the PCB from dirt and damage.

### Strain relief

The integrated strain relief fixes the cable in the enclosure.



## Specification

- Connectors:  
1 x serial Sub-D 9 male with screws  
1 x 10 pin terminal block
- Pin assignment: 1:1
- Pitch: 3.81 mm
- Useable for a cable gauge from 26 to 18 AWG
- Operating temperature: -20 °C ~ 105 °C
- Dimensions (LxWxH): ca. 51.8 x 34.4 x 21.0 mm

## Item no. 66232

EAN: 4043619662326

Country of origin: CHINA

Package: • Zip poly bag



## System requirements

- A free Sub-D 9 pin female

## Package content

- Adapter
- 1 x strain relief
- 2 x locking screws

## Images



Interface	
Connector 1:	1 x serial Sub-D 9 male with screws
Connector 2:	1 x 10 pin terminal block
Technical characteristics	
Operating temperature:	-20 °C ~ 105 °C
Physical characteristics	
Pitch distance:	3.81 mm
Conductor gauge:	26 - 18 AWG
Length:	51.8 mm
Width:	34.4 mm
Height:	21.0 mm