



Delock Desktop USB Gaming Microphone with Gooseneck and Mute Button

Description

This USB microphone by Delock can be used for voice and vocal transmissions.

Optimal recordings

The microphone has a circle pattern (omnidirectional) and therefore captures the acoustic signal ideally. Due to a high power, low self-noise and precise performance, even the finest sounds are optimally recorded.

Mute button & blue LED light

With the star shaped mute button in the middle of the microphone, the microphone can be muted very quickly. In mute mode the LEDs are switched off. In addition, the microphone has a switch on the side, which can be used to completely deactivate or reactivate the LEDs.

Flexible gooseneck

With the gooseneck, the microphone can be bent in the preferred direction.

Headphone output

The microphone has a 3.5 mm stereo jack output at the rear for connection of e.g. headphones or speakers.

Rugged cable

The 1.5 m long USB cable has a braided sleeving and a gold-plated USB plug and is therefore very rugged and has a high resistance to disturbances.

Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as Windows, Mac OS, Chrome OS and Linux.

Specification

- · Connectors:
- 1 x USB 2.0 Type-A male
- 1 x 3.5 mm 3 pin stereo jack female
- · Directivity: omnidirectional
- Sensitivity: -30 dB +/- 3 dB
- Frequency range: 50 Hz 16 kHz
- Sample rate: 16 Bit / 44.1 kHz
- Signal-to-noise ratio (SNR): ca. 60 dB
- Impedance: 2.2 kOhm
- Mute-Button
- · LED on / off button
- Cable length: ca. 1.5 m
- · Colour: black / blue
- Dimensions (LxWxH): ca. 108 x 97 x 325 mm
- USB bus powered
- Plug & Play

System requirements

- Chrome OS
- · Linux Kernel 4.4 or above
- · Mac OS 10.9 or above



Item no. 66330

EAN: 4043619663309

Country of origin: China

Package: • Retail Box







- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- User manual

Images











Function: Plug & Play Supported operating system: Chrome OS Mac OS 10.9 or above Windows 7 32-bit Windows 7 32-bit Windows 8 4-bit Windows 8 32-bit Windows 8.1 32-bit Windows 8.1 54-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 4.4 or above LED indicator: 2 x Interface I x USB 2.0 Type-A male Technical characteristics Frequency range: Trequency range: 50 Hz - 16 kHz Voltage: USB bus powered Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue LED colour: blue	General	
Mac OS 10.9 or above Windows 7 32-bit Windows 7 64-bit Windows 8 32-bit Windows 8 44-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 4.4 or above LED indicator: 2 x Interface connector: 1 x USB 2.0 Type-A male Technical characteristics Frequency range: 50 Hz - 16 kHz Voltage: USB bus powered Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue	Function:	Plug & Play
Windows 7 32-bit	Supported operating system:	Chrome OS
Windows 7 64-bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 4.4 or above LED indicator: 2 x Interface connector: 1 x USB 2.0 Type-A male Technical characteristics Frequency range: 50 Hz - 16 kHz Voltage: USB bus powered Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue		Mac OS 10.9 or above
Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 4.4 or above LED indicator: 2 x Interface connector: 1 x USB 2.0 Type-A male Technical characteristics Frequency range: 50 Hz - 16 kHz Voltage: USB bus powered Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue		Windows 7 32-bit
Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 4.4 or above LED indicator: 2 x Interface connector: 1 x USB 2.0 Type-A male Technical characteristics Frequency range: 50 Hz - 16 kHz Voltage: USB bus powered Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue		Windows 7 64-bit
Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 4.4 or above LED indicator: 2 x Interface connector: 1 x USB 2.0 Type-A male Technical characteristics Frequency range: 50 Hz - 16 kHz Voltage: USB bus powered Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue		Windows 8 32-bit
Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 4.4 or above LED indicator: 2 x Interface connector: 1 x USB 2.0 Type-A male Technical characteristics Frequency range: 50 Hz - 16 kHz Voltage: USB bus powered Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 1.5 m Length: 1.5 m Height: 325 mm Colour: black / blue		Windows 8 64-bit
Windows 10 32-bit Windows 10 64-bit Linux Kernel 4.4 or above LED indicator: 2 x Interface connector: 1 x USB 2.0 Type-A male Technical characteristics Frequency range: 50 Hz - 16 kHz Voltage: USB bus powered Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue		Windows 8.1 32-bit
Windows 10 64-bit Linux Kernel 4.4 or above LED indicator: 2 x Interface Interface connector: 1 x USB 2.0 Type-A male Technical characteristics Frequency range: 50 Hz - 16 kHz Voltage: USB bus powered Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue		Windows 8.1 64-bit
Linux Kernel 4.4 or above LED indicator: 2 x Interface connector: 1 x USB 2.0 Type-A male Technical characteristics Frequency range: 50 Hz - 16 kHz Voltage: USB bus powered Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue		Windows 10 32-bit
LED indicator: 2 x Interface 1 x USB 2.0 Type-A male Technical characteristics Frequency range: 50 Hz - 16 kHz Voltage: USB bus powered Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue		Windows 10 64-bit
Interface connector: 1 x USB 2.0 Type-A male Technical characteristics Frequency range: 50 Hz - 16 kHz Voltage: USB bus powered Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue		Linux Kernel 4.4 or above
Technical characteristics Frequency range: 50 Hz - 16 kHz Voltage: USB bus powered Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue	LED indicator:	2 x
Technical characteristics Frequency range: 50 Hz - 16 kHz Voltage: USB bus powered Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue	Interface	
Frequency range: 50 Hz - 16 kHz Voltage: USB bus powered Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue	connector:	1 x USB 2.0 Type-A male
Voltage: USB bus powered Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue	Technical characteristics	
Sensibility: -30 dB +/- 3 dB Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue	Frequency range:	50 Hz - 16 kHz
Sample rate: 16 Bit / 44.1 kHz Signal noise ratio (SNR): ca. ≥ 60dB Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue	Voltage:	USB bus powered
Signal noise ratio (SNR):ca. ≥ 60dBDirectivity:omnidirectionalPhysical characteristicsCable length:1.5 mLength:108 mmWidth:97 mmHeight:325 mmColour:black / blue	Sensibility:	-30 dB +/- 3 dB
Directivity: omnidirectional Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue	Sample rate:	16 Bit / 44.1 kHz
Physical characteristics Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue	Signal noise ratio (SNR):	ca. ≥ 60dB
Cable length: 1.5 m Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue	Directivity:	omnidirectional
Length: 108 mm Width: 97 mm Height: 325 mm Colour: black / blue	Physical characteristics	
Width: 97 mm Height: 325 mm Colour: black / blue	Cable length:	1.5 m
Height: 325 mm Colour: black / blue	Length:	108 mm
Colour: black / blue	Width:	97 mm
	Height:	325 mm
LED colour: blue	Colour:	black / blue
	LED colour:	blue