

# Delock USB 2.0 to serial RS-232 adapter with compact serial connector housing 50 cm FTDI

## Description

This USB 2.0 Type-A to serial adapter by Delock provides an RS-232 port for meters, POS systems, printers, modems, IoT devices, etc.

### User-friendly RS-232 plug

The RS-232 connector is characterized by its small dimensions (39,0 x 33,0 x 14,7 mm) and provides a pleasant handling at device connections, cable glands, patch panels, etc.



50 cm

**Item no. 66453**

EAN: 4043619664535

Country of origin: China

Package:

## Specification

- Connectors:
  - 1 x USB 2.0 Type-A male
  - 1 x serial RS-232 DB9 female with nuts
- Chipset: FTDI FT232R
- Data transfer rate up to 921.6 Kbps
- Signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Parity: even, odd, none, mark, space
- Stop bits: 1, 2
- Databits: 7, 8
- Flow control: none, Xon / Xoff, RTS / CTS
- FIFO: 128 Byte - RX
- FIFO: 256 Byte - TX
- Cable length incl. connectors: ca. 50 cm

## System requirements

- Chrome OS

- Linux Kernel 5.15 or above
- Mac OS 12.4 or above
- Windows 10/10-64/11
- PC or laptop with a free USB Type-A port

---

## Package content

- USB 2.0 to 1 x serial adapter
- Driver CD
- User manual

---

## Images



## General

Function:	Plug & Play
Specification:	RS-232 (EIA / TIA) USB 2.0
Supported operating system:	Linux Kernel 2.6 or above Mac OS 10.9 or above Windows 10 32-bit Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 11

## Interface

Connector 1:	1 x USB 2.0 Type-A male
Connector 2:	1 x Serial RS-232 DB9 female

## Technical characteristics

Chipset:	FTDI 232R
Data transfer rate:	up to 921.6 Kbps
FIFO:	128 byte 256 Byte
Data transmission:	asynchronous Bi-directional
UART:	USB to serial UART

## Physical characteristics

Cable length:	50 cm
Pin finishing:	gold-plated
Shielding:	double
Colour:	black



