

# Delock USB 2.0 to serial RS-232 adapter with compact serial connector housing 50 cm FTDI

## Description

This USB 2.0 Type-A to serial adapter by Delock provides an RS-232 port for meters, POS systems, printers, modems, IoT devices, etc.

### User-friendly RS-232 plug

The RS-232 connector is characterized by its small dimensions (39,0 x 33,0 x 14,7 mm) and provides a pleasant handling at device connections, cable glands, patch panels, etc.



50 cm

**Item no. 66461**

EAN: 4043619664610

Country of origin: China

Package:

## Specification

- Connectors:
  - 1 x USB 2.0 Type-A male
  - 1 x serial RS-232 DB9 male with screws
- Chipset: FTDI FT232R
- Data transfer rate up to 921.6 Kbps
- Signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Parity: even, odd, none, mark, space
- Stop bits: 1, 2
- Databits: 7, 8
- Flow control: none, Xon / Xoff, RTS / CTS
- FIFO: 128 Byte - RX
- FIFO: 256 Byte - TX
- Cable length incl. connectors: ca. 50 cm

## System requirements

- Chrome OS

- Linux Kernel 5.15 or above
- Mac OS 12.4 or above
- Windows 10/10-64/11
- PC or laptop with a free USB Type-A port

---

## Package content

- USB 2.0 to 1 x serial adapter
- Driver CD
- User manual

---

## Images



## General

|                             |   |
|-----------------------------|---|
| Function:                   | Plug & Play   |
| Specification:              | RS-232 (EIA / TIA)<br>USB 2.0   |
| Supported operating system: | Linux Kernel 2.6 or above<br>Mac OS 10.9 or above<br>Windows 10 32-bit<br>Windows 10 64-bit<br>Windows 7 32-bit<br>Windows 7 64-bit<br>Windows 8.1 32-bit<br>Windows 8.1 64-bit<br>Windows 11 |

## Interface

|              |                            |
|--------------|----------------------------|
| Connector 1: | 1 x USB 2.0 Type-A male    |
| Connector 2: | 1 x Serial RS-232 DB9 male |

## Technical characteristics

|                     |                                |
|---------------------|--------------------------------|
| Chipset:            | FTDI 232R                      |
| Data transfer rate: | up to 921.6 Kbps               |
| FIFO:               | 128 byte<br>256 Byte           |
| Data transmission:  | asynchronous<br>Bi-directional |
| UART:               | USB to serial UART             |

## Physical characteristics

|                               |             |
|-------------------------------|-------------|
| Cable length incl. connector: | 50 cm       |
| Pin finishing:                | gold-plated |
| Shielding:                    | double      |
| Colour:                       | black       |



