



Delock HDMI Switch 3 x HDMI in to 1 x HDMI out 4K 60 Hz with Audio Extractor

Description

With this HDMI switch by Delock up to **three HDMI devices** can be used with one HDMI monitor, TV or projector. The button on the device or the remote control can be used to switch between the HDMI devices.

Audio extractor

This function can be used to extract the audio signal from an HDMI transmission. While the video signal is displayed on a TV or monitor, the audio signal can be sent **digital** (S/PDIF) or analogue (stereo) to other devices, such as headphones or a surround receiver.

Audio Return Channel (ARC)

ARC can be enabled at the push of a button on the device or the remote control. Then the **audio signal of the connected TV** device is routed to the S/PDIF connectors of the switch.



Specification

· Connectors:

Input:

3 x HDMI-A female

1 x DC 5 V power connector

Output:

1 x HDMI-A female

2 x RCA female (audio)

1 x TOSLINK female S/PDIF

1 x RCA female S/PDIF

- HDMI port switching: automatic function, via button or via infrared remote control
- LED indicators for active HDMI port
- High Speed HDMI specification
- Supports 3D displays
- Supports HDCP 1.4 and 2.2
- Supports HDR
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Video bandwidth up to 600 MHz / 6 Gbps, max. 18 Gbps
- Power consumption: max. 5 W
- · Metal housing
- Removable wallmount brackets
- Colour: black
- Dimensions (LxWxH): ca. 168 x 75 x 21 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- · Ground outside, plus inside
- · Dimensions:

inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 9 mm

System requirements

- · A free HDMI female
- HDMI cable

Item no. 66498

EAN: 4043619664986

Country of origin: China

Package: • Retail Box







Package content

- HDMI switch
- Remote control
- Mounting brackets and screws
- USB power cable, length: ca. 0.5 m
- Power supply
- User manual

Images













General	
Specification:	High Speed HDMI
	HDCP 1.4
	HDCP 2.2
	HDR
Interface	
Output:	1 x RCA female
	1 x HDMI-A 19 pin female
	1 x TOSLINK female S/PDIF
	2 x RCA female (red, white)
Input:	1 x 5 V DC female 5,5 mm x 2,1 mm
	3 x HDMI-A 19 pin female
Technical characteristics	
Maximum screen resolution:	3840 x 2160 @ 60 Hz
Physical characteristics	
Housing colour:	black
Housing material:	metal
Length:	168 mm
Width:	75 mm
Height:	21 mm
Power supply	
Type:	Euro wall power supply
Input:	AC 100 - 240 V / 50 - 60 Hz / 0.5 A
Output:	5 V / 1 A
Connector:	