

Delock MDR male 14 pin solder connection with housing

Description


This shielded MDR (Mini D Ribbon) male with soldering connection by Delock can be used for cable mounting and I/O applications.

Protection by enclosure

The plastic housing protects the male connector from dirt and damage.

Strain relief

The screw-on strain relief fixes the cable in the enclosure.



Item no. 66621

EAN: 4043619666218

Country of origin: China

Package: Zip poly bag

Specification

- Connectors: 1 x MDR 14 male (2 rows) with soldering connection
- Pitch: 1.27 mm
- Useable for a cable gauge from 30 to 24 AWG
- Contact coating: gold plated, nickel plated
- Operating temperature: -25 °C ~ 85 °C
- Fire-resistance rating: 94V-0
- Housing material: plastic
- Dimensions (LxWxH): ca. 39.0 x 29.5 x 12.7 mm

Package content

- MDR male
- Housing 2-part
- Strain relief 2-part
- 4 x screw
- 2 x locking screws
- 2 x nut

Interface

connector:	MDR 14 male (2 rows) with soldering connection
------------	------------------------------------------------

Technical characteristics

Operating temperature:	-25 °C ~ 85 °C
------------------------	----------------

Physical characteristics

Pitch distance:	1.27 mm
Housing material:	Plastic
Conductor gauge:	30 - 24 AWG
Length:	39,0 mm
Width:	29.5 mm
Height:	12.7 mm