

# Delock USB Tie Lavalier Microphone Omnidirectional 24 bit / 192 kHz with clip and 3.5 mm stereo jack headphone port

## Description

This USB microphone by Delock can be used for high-quality voice and vocal transmissions.

### With clip to attach

It can easily be **clipped** to a **tie** or **collar**.

### Optimal recordings

The microphone has a **circle pattern (omnidirectional)** and therefore captures the acoustic signal ideally. Due to a high performance, low self-noise and precise performance, even the finest sounds are optimally recorded.

### High sampling rate

Typical USB microphones work with 16 Bit and 44 kHz. This Delock microphone offers a sampling rate of **24 bit** and **192 kHz**, so it is possible to record in **Hi-Fi studio quality**.

### High-Res audio headphone output

The microphone has a **3.5 mm stereo jack** female port for connecting e.g. headphones or loudspeakers, for example. The audio output provides a bit depth of **32 bits** at a **sampling rate** of **192 kHz**.

### Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as **Windows**, **Mac OS**, **Chrome OS** and **Linux**.



## Specification

- Connectors:  
1 x USB 2.0 Type-A male  
1 x 3.5 mm 3 pin stereo jack female
- Directivity: omnidirectional
- Sensitivity: -30 dB +/- 3 dB
- Frequency range: 50 Hz - 18 kHz
- Sampling rates:  
recording up to 24 bit / 192 kHz  
playback up to 32 bit / 192 kHz
- Signal-to-noise ratio (SNR): ca. 74 dB
- Cable length: ca. 2 m
- Housing material: metal
- Colour: black / anthracite
- Weight: ca. 30 g
- USB bus powered
- Plug & Play

## System requirements

- Chrome OS
- Linux Kernel 3.3 or above
- Mac OS 10.14 or above
- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

## Package content

- USB microphone

## Item no. 66638

EAN: 4043619666386

Country of origin: China

Package: • Retail Box

- Clip
- Windscreen
- Storage bag
- User manual

Images



**General**

Function:	Plug & Play
Supported operating system:	Chrome OS Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 3.3 or above Mac OS 10.14 or above

**Interface**

Connector 1:	1 x 3.5 mm 3 pin stereo jack female 1 x USB 2.0 Type-A male
--------------	--

**Technical characteristics**

Frequency range:	50 Hz - 18 kHz
Voltage:	USB bus powered
Sensibility:	-30 dB +/- 3 dB
Sample rate:	24 Bit / 192 kHz
Signal noise ratio (SNR):	ca. 74 dB
Directivity:	omnidirectional

**Physical characteristics**

Weight:	30 g
Cable length:	2 m
Colour:	anthracite black