

# Delock Adapter D-Sub 9 pin female with nuts to D-Sub 25 pin male with screws

## Description

This narrow adapter by Delock can, for example, connect devices such as printers, modems and computers with serial RS-232 D-Sub 9 or D-Sub 25 interfaces.



## Specification

- Connectors:  
1 x D-Sub 9 pin female with nuts  
1 x D-Sub 25 pin male with screws
- Pin assignment: 1 - 8, 2 - 3, 3 - 2, 4 - 20, 5 - 7, 6 - 6, 7 - 4, 8 - 5, 9 - 22, shielded
- Contacts: gold plated brass
- Screw type: #4-40 UNC
- Dimensions (LxWxH): ca. 53 x 18 x 13 mm

## System requirements

- A free D-Sub 9 pin interface
- A free D-Sub 25 pin interface

## Package content

- Adapter D-Sub 9 pin to D-Sub 25 pin

## Item no. 66981

EAN: 4043619669813

Country of origin: Taiwan, Republic of China

Package: Zip poly bag

## Images

DB 9 Pin	Name	DB 25 Pin
1	DCD	8
2	RXD	3
3	TXD	2
4	DTR	20
5	GND	7
6	DSR	6
7	RTS	4
8	CTS	5
9	RI	22

<b>Interface</b>	
Connector 1:	1 x Serial D-Sub 9 female with nuts
Connector 2:	1 x Serial D-Sub 25 male mit screws
<b>Technical characteristics</b>	
Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
<b>Physical characteristics</b>	
Pin finishing:	gold-plated
Screw type:	#4-40 UNC
Material:	metal / plastic
Length:	53 mm
Width:	18 mm
Height:	13 mm
Colour:	silver / orange