

Delock Adapter D-Sub 9 pin female with nuts to D-Sub 25 pin female with screws

Description

This narrow adapter by Delock can, for example, connect devices such as printers, modems and computers with serial RS-232 D-Sub 9 or D-Sub 25 interfaces.



Specification

- Connectors:
 - 1 x D-Sub 9 pin female with nuts
 - 1 x D-Sub 25 pin female with screws
- Pin assignment: 1 - 8, 2 - 3, 3 - 2, 4 - 20, 5 - 7, 6 - 6, 7 - 4, 8 - 5, 9 - 22, shielded
- Contacts: gold plated brass
- Screw type: #4-40 UNC
- Dimensions (LxWxH): ca. 53 x 18 x 13 mm

System requirements

- A free D-Sub 9 pin interface
- A free D-Sub 25 pin interface

Package content

- Adapter D-Sub 9 pin to D-Sub 25 pin

Item no. 66983

EAN: 4043619669837

Country of origin: Taiwan, Republic of China

Package: Zip poly bag

Images

| DB 9 Pin | Name | DB 25 Pin |
|----------|------|-----------|
| 1 | DCD | 8 |
| 2 | RXD | 3 |
| 3 | TXD | 2 |
| 4 | DTR | 20 |
| 5 | GND | 7 |
| 6 | DSR | 6 |
| 7 | RTS | 4 |
| 8 | CTS | 5 |
| 9 | RI | 22 |

| | |
|----------------------------------|--|
| Interface | |
| Connector 1: | 1 x Serial D-Sub 9 female with nuts |
| Connector 2: | 1 x Serial D-Sub 25 female with screws |
| Technical characteristics | |
| Signal transmission: | TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND |
| Physical characteristics | |
| Pin finishing: | gold-plated |
| Screw type: | #4-40 UNC |
| Material: | metal / plastic |
| Length: | 53 mm |
| Width: | 18 mm |
| Height: | 13 mm |
| Colour: | silver / orange |