



Delock M8 3 pin Cable A-coded male to female PUR (TPU) 1 m

Description

This industrial Ethernet cable by Delock can be used to connect various components with M8 connectors, e.g. for machine control or automation.

Durable TPU cable jacket

The material of the cable jacket makes the cable flexible and durable, making it suitable for use in drag chains and harsh environments.

The cable is oil and UV resistant and meets the high requirements for industrial applications.



1 m

ltem no. 80138

EAN: 4043619801381

Country of origin: China

Package: Zip poly bag

Specification

Connectors:

- 1 x M8 male 3 pin A-coded
- 1 x M8 female 3 pin A-coded
- Pin assignment: 1:1
- · Shielding: aluminium foil, tinned copper braiding
- Copper cable
- Cable gauge: 24 AWG
- Cable diameter: ca. 4.6 mm
- Cable jacket material: PUR (TPU)
- Max. number of bending cycles: >100
- UV-resistant
- Operating temperature: -25 °C ~ 80 °C
- Protection class: IP67
- Colour: black
- Length incl. connectors: ca. 1 m

System requirements

A free M8 port

Package content

Patch cable

Images







General	
Protection category:	IP67
Interface	
Connector 1:	1 x M8 male
Connector 2:	1 x M8 female
Technical characteristics	
Operating temperature:	-25 °C ~ 85 °C
Physical characteristics	
Cable diameter:	4.6 mm
Conductor gauge:	24 AWG
Length:	1 m