



Cable DisplayPort 1.2 male > High Speed HDMI-A male passive 4K 30 Hz 5 m black

Description

This cable by Delock enables the connection between devices, e.g. a monitor, with HDMI connector to a DisplayPort interface.



ltem no. 85319

EAN: 4043619853199

Country of origin: China

Package: Zip poly bag

Specification

Connectors:

- 1 x DisplayPort 20 pin male >
- 1 x High Speed HDMI-A 19 pin male
- Chipset: Parade PS8402A
- DisplayPort 1.2a and High Speed HDMI specification
- Passive cable (level shifter), suitable only for graphics cards with DP++ output
- Signal direction: DisplayPort input > HDMI output
- Cable gauge: 30 AWG
- Cable diameter: ca. 6 mm
- Twisted-pair cabling
- · Copper conductor
- · Gold-plated connectors
- Triple shielded cable
- Transfer of audio and video signals
- Data transfer rate up to 10.2 Gb/s
- Resolution up to 3840 x 2160 @ 30 Hz
- (depending on the system and the connected hardware)
- Colour: black
- · Length incl. connectors: ca. 5 m

System requirements

One free DisplayPort DP++ female

Package content

DisplayPort to HDMI cable

Images







General	
Specification:	DisplayPort 1.2a
	High Speed HDMI
Interface	<u> </u>
Connector 1:	1 x DisplayPort male
Connector 2:	1 x HDMI-A male
Technical characteristics	
Chipset:	Parade PS8402A
Data transfer rate:	10.2 Gb/s
Maximum screen resolution:	3840 x 2160 @ 30 Hz
Physical characteristics	
Cable diameter:	6 mm
Connector finishing:	gold-plated
Pin finishing:	gold-plated
Conductor material:	copper
Conductor gauge:	30 AWG
Shielding:	triple
Length:	5 m
Colour:	black