

Delock Cable USB 3.1 Gen 2 key A 20 pin male > USB 3.1 Gen 2 Type-A female panel-mount 70 cm

Description

This cable by Delock can be connected to the internal USB 3.1 Gen 2 key A socket of a motherboard or a PCI Express card (e.g. [Delock 89603](#)) and can be used to extend a USB connection. The USB Type-A connector can be attached with two screws, e.g. on a slot bracket or a chassis with the corresponding recess. In this way, it is possible to install a USB port in an easily accessible position.



ca. 70 cm

Specification

- Connectors:
 - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) key A 20 pin male 90° angled >
 - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type-A female
- Two mounting holes for screws, spacing 31 mm, with M3 thread
- Cable gauge:
 - 28 + 30 AWG data line
 - 26 + 28 AWG power line
- Resistor: 5.1 kΩ
- Cable diameter: ca. 6 mm
- Data transfer rate up to:
 - SuperSpeed USB 10 Gbps,
 - SuperSpeed USB 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- Length incl. connectors: ca. 70 cm

System requirements

- PC with a free USB 3.1 Gen 2 key A interface

Package content

- USB cable

Item no. 85325


EAN: 4043619853250

Country of origin: China

Package: • Zip poly bag



Images



Interface	
Connector 1:	1 x USB 3.1 Gen 2 key A 20 pin male
Connector 2:	1 x USB 3.1 Gen 2 type-A female
Technical characteristics	
Data transfer rate:	SuperSpeed USB 10 Gbps
Resistor:	5.1 kΩ
Physical characteristics	
Cable diameter:	6 mm
Conductor gauge:	28 AWG data line
	30 AWG data line
	26 AWG power line
	28 AWG power line
Length:	70 cm