

Delock PoweredUSB cable male 24 V > USB Type-B male + Hosiden Mini-DIN 3 pin male 3 m for POS printers and terminals

Description

This PoweredUSB cable by Delock can be used to connect a device with USB Type-B port and Hosiden Mini-DIN 3 pin power port to a PC or hub with PoweredUSB 24 V port. It is suitable for connecting various POS devices such as printers and terminals, e.g. by **Epson** or **Toshiba**. The cable is used both for data transmission and for power supply of the connected device.



3 m

Item no. 85489

EAN: 4043619854899

Country of origin: China

Package: Zip poly bag

Specification

- Connectors:
 - 1 x PoweredUSB male 24 V >
 - 1 x USB Type-B male +
 - 1 x Hosiden Mini-DIN 3 pin power male
- PoweredUSB specification
- Voltage: 24 V
- Cable gauge:
 - 26 AWG data line
 - 20 AWG power line
- Cable diameter: ca. 6.5 mm
- Cable double shielded
- Data transfer rate up to 480 Mbps
- Colour: black
- Length incl. connectors (L): ca. 3 m


System requirements

- PC or hub with a free PoweredUSB 24 V female port
- Device with a free USB Type-B port and a free Hosiden Mini-DIN 3 pin power female port

Package content

- PoweredUSB cable

Images



General

Specification:	PoweredUSB
----------------	------------

Interface

Connector 1:	1 x PoweredUSB male 24 V
Connector 2:	1 x USB 2.0 Type-B mBle 1 x Hosiden Mini-DIN 3 pin male

Technical characteristics

Data transfer rate:	USB 2.0 up to 480 Mb/s
Voltage:	24 V

Physical characteristics

Cable diameter:	6.5 mm
Conductor gauge:	26 AWG data line 20 AWG power line
Shielding:	double
Length:	3 m
Colour:	black