



# Delock USB-CTM, HDMI or mini DisplayPort to 4K HDMI Adapter Cable 1.8 m

#### Description

This adapter cable by Delock can be used to connect a projector or monitor with HDMI input to a laptop with **HDMI**, **USB Type-C™** or **mini DisplayPort** interface.

#### Ideal for conference room

By using this cable solution, no additional adapter is required in the conference room. The corresponding connector can be used depending on the user's requirements. The adapter can also be used in classrooms or lecture theatres, where the tutor can simply connect the laptop to the appropriate port.

#### **HDMI Ultra HD resolution**

The HDMI output supports a maximum resolution of up to 3840 x 2160 pixels at 60 Hz, furthermore the audio signals can also be transmitted.



## 1,80 m

## **Specification**

· Connectors:

Input:

- 1 x USB Type-C™ male
- 1 x HDMI-A male
- 1 x mini DisplayPort male
- 1 x USB Type Micro-B female (5 V power supply DisplayPort and HDMI) Output:
- 1 x HDMI-A male
- Chipset: ITE IT66351, IT6350E, IT6563FN, Realtek RTD2172U
- Resolution up to 3840 x 2160 @ 60 Hz

(depending on the system and the connected hardware)

- · Transmission of audio and video signals
- · LED indicator for active port
- · Colour: black
- · Cable length input: ca. 30 cm
- Cable length output: ca. 145 cm

## System requirements

- Android 8.0 or above
- Chrome OS 72.0 or above
- iPad Pro (2018)
- · Linux Kernel 4.3 or above
- Mac OS 10.9.5 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- Device with a free USB Type-C<sup>™</sup> port and DisplayPort alternate mode or with a free Thunderbolt™ 3 port or
- · A free HDMI female or
- A free mini DisplayPort female

### Package content

- · Adapter cable
- USB power cable, length: ca. 0.5 m
- User manual

#### Item no. 85830

EAN: 4043619858309

Country of origin: China

Package: Retail Box







## Images







General	
Supported operating system:	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	Android 8.0 or above
	Linux Kernel 4.3 or above
	Mac OS 10.9.5 or above
	iPad Pro (2018)
	Chrome OS 72.0 or above
Interface	
Output:	1 x HDMI-A 19 pin male
Input:	1 x HDMI-A 19 pin male
	1 x mini DisplayPort 20 pin male
	1 x USB Type-C™ male
Technical characteristics	
Maximum screen resolution:	3840 x 2160 @ 60 Hz
Physical characteristics	
Cable length:	input: ca. 30 cm
	output: ca. 145 cm
Colour:	black