

Delock USB Type-CTM Splitter (DP Alt Mode) > 1 x HDMI + 1 x VGA out

Description

This splitter by Delock is suitable for the connection of a VGA monitor and an HDMI monitor to a computer with USB-CTM interface and DisplayPort alternate mode support. Two monitors can be operated simultaneously at the outputs, the same image is displayed on all ports.



Specification

Connectors:

Input:

1 x USB Type-C™ male

Output:

1 x HDMI-A 19 pin female

- 1 x VGA 15 pin female
- VGA port with nuts
- · DisplayPort 1.2 specification
- HDMI

Resolution up to 2560 x 1440 @ 60 Hz / 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)

VGA:

Resolution up to 1920 x 1080 @ 60 Hz (depending on the system and the connected hardware)

- Function: Mirrored
- · USB bus powered
- Cable length incl. connectors: ca. 20 cm
- Dimensions (LxWxH): ca. 87 x 40 x 16 mm

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Windows 10 Mobile, Chrome OS, ex Linux Kernel 4.9, ex Mac OS 10.12
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

Package content

- USB-CTM Splitter (DP Alt Mode)
- User manual

Images







Item no. 87730

EAN: 4043619877300

Country of origin: China

Package: Retail Box







| General | |
|-------------------------------|--------------------------|
| Specification: | DisplayPort 1.2 |
| | USB Type-C™ |
| Supported operating system: | Mac OS 10.9 or above |
| | Windows 8.1 32-bit |
| | Windows 8.1 64-bit |
| | Windows 10 32-bit |
| | Windows 10 64-bit |
| Interface | |
| Output: | 1 x HDMI-A 19 pin female |
| | 1 x VGA 15 pin female |
| Input: | 1 x USB Type-C™ male |
| Technical characteristics | |
| Maximum screen resolution: | 3840 x 2160 @ 30 Hz |
| Physical characteristics | |
| Housing colour: | silver |
| Housing material: | metal |
| Cable length incl. connector: | 10 cm |
| Length: | 87 mm |
| Width: | 40 mm |
| Height: | 16 mm |