

# Delock Multi-AV to HDMI Converter 4K 60 Hz

## Description

This multi-functional converter by Delock makes it possible to convert different sources into one HDMI signal. The signal inputs are USB-C™ (DP Alt Mode), VGA with 3.5 mm audio, Mini DisplayPort and HDMI. The converter box is a practical solution for connecting various audio / video devices to a projector or TV with HDMI input.

4K  
60Hz



## Specification

- Connectors:
  - Input:
    - 1 x mini DisplayPort 20 pin female
    - 1 x HDMI-A 19 pin female
    - 1 x USB Type-C™ (DP Alt Mode) female
    - 1 x VGA 15 pin female with nuts
    - 1 x 3.5 mm 3 pin stereo jack female
    - 1 x DC 5 V power connector
    - 1 x RJ45 jack
  - Output:
    - 1 x HDMI-A 19 pin female
    - 1 x RJ45 jack
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Resolution (VGA input) up to 1920 x 1080 @ 60 Hz
- Transmission of audio and video signals
- Switching automatic or via button
- Robust metal housing
- Dimensions (LxWxH): ca. 179 x 80 x 25 mm

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.5 A
- Output: 5 V / 2.5 A
- Ground outside, plus inside
- Dimensions:
  - inside: ø ca. 2.5 mm
  - outside: ø ca. 5.5 mm
  - length: ca. 9.5 mm

## Package content

- Converter
- Mounting bracket
- Power supply
- User manual

## Item no. 87732


EAN: 4043619877324

Country of origin: Taiwan, Republic of China

Package: • Retail Box



Images



**Interface**

<b>Output:</b>	1 x RJ45 jack 1 x HDMI-A 19 pin female
<b>Input:</b>	1 x HDMI-A 19 pin female 1 x mini DisplayPort 20 pin female 1 x 3.5 mm 3 pin stereo jack female 1 x RJ45 jack 1 x USB type-C™ female 1 x VGA 15 pin female 1 x DC female

**Technical characteristics**

<b>Maximum screen resolution:</b>	3840 x 2160 @ 60 Hz
-----------------------------------	---------------------

**Physical characteristics**

<b>Length:</b>	179 mm
<b>Width:</b>	80 mm
<b>Height:</b>	25 mm