

# Delock Serial Cable RS-232 D-Sub 9 female to female null modem with narrow plug housing - CTS / RTS auto control - 2 m

## Description

This serial cable by Delock is a **fully wired null modem cable** with - CTS / RTS auto control - for printers, measuring instruments, converters, RS-232 hubs, patch panels etc. With this cable, two serial RS-232 devices can be connected to each other for data exchange.

### Mini D-Sub 9 connector

These cables fit on any RS-232 port, as the **mini D-Sub 9 connectors** (44 x 33.3 x 15 mm) are small and compact. In this way, RS-232 connections can be used directly adjacent to each other.



2 m

**Item no. 87785**

EAN: 4043619877850

Country of origin: China

Package: Zip poly bag

## Specification

- Connectors:
  - 1 x serial D-Sub 9 female with screws
  - 1 x serial D-Sub 9 female with screws
- Cable gauge: 28 AWG
- Full handshaking cable
- Pin assignment: 7+8 - 1, 2 - 3, 3 - 2, 4 - 6, 6 - 4, 5 - 5, 1 - 7+8, shielded
- Colour: black
- Insulator: PVC
- Screw type: #4-40 UNC
- Cable diameter: ca. 5 mm
- Cable length incl. connectors: ca. 2 m



## System requirements

- A free D-Sub 9 male port

## Package content

- Cable

## Images



## General

Specification:	RS-232 (EIA / TIA)
Style:	Mini Sub-D9 Nullmodem "RTS / CTS auto control"

## Interface

Connector 1:	1 x serial D-Sub 9 female with screws
Connector 2:	1 x serial D-Sub 9 female with screws

## Technical characteristics

Data transfer rate:	up to 921.6 Kbps
Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND + Schirmung

## Physical characteristics

Cable type:	AWM Style 2464 28 AWG 80 °C 300 V VW-1
Cable diameter:	5 mm
Cable length incl. connector:	2 m
Pin finishing:	gold-plated
Conductor material:	Copper tinned
Conductor gauge:	28 AWG
Screw type:	#4-40 UNC
Shielding:	Aluminum foil
Colour:	black
Cable jacket material:	PVC
Safety of Flammability:	VW-1