

# Delock USB 2.0 Fast Charging Cable USB Type-C<sup>™</sup> + USB Type-A male to USB Type-C<sup>™</sup> male PD 3.1 140 W with power indication 1.20 m

#### Description

This USB cable by Delock enables the connection between a device with a USB Type-C<sup>™</sup> connector and a PC or a laptop equipped with a free USB Type-C<sup>™</sup> or USB Type-A port. The integrated chipset supports the PD 3.1 function for fast charging with a charging power of up to 140 W.

#### Display

A special feature of this cable is the **power indication**, which shows the current charging power.

#### **Extensive connectivity**

Due to the specially designed adapter, the Delock cable can be quickly and easily connected to the USB Type-A socket. Thus, it can be easily connected to new devices with USB Type-C<sup>™</sup> female and older devices that only have a USB Type-A connector. The adapter is located directly on the cable and therefore it cannot be lost.

#### Quality and performance

The cable is very sturdy and durable due to its robust textile shielding and strong strain relief. The high cable gauge of the power line with 20 AWG also supports a stable power supply of up to 5 A.

## Specification

Connectors:

1 x USB Type-C<sup>TM</sup> + USB Type-A male 1 x USB Type-C<sup>TM</sup> male

- Chipset: BJ8M601AFE-BK1
- Cable gauge:

28 AWG data line

20 AWG power line

- Power supply via USB Type-CTM up to 140.0 W (28.0 V / 5.0 A)
- Power supply via USB Type-A up to 60.0 W (20.0 V / 3.0 A)



2 m

#### **DATASHEET**



- USB Power Delivery (USB PD 3.1) support up to 140.0 watt (only via USB Type-C™)
- Cable diameter: ca. 3.8 mm
- Data transfer rate up to 480 Mbps
- Cable with textile shielding
- Colour: black
- Length incl. connectors: ca. 1.20 m

## System requirements

- PC or laptop with a free USB Type-C<sup>™</sup> or USB Type-A port
- Power supply with a free USB Type-C<sup>™</sup> or USB Type-A port
- Device with USB Type-C<sup>™</sup> port

## Package content

• Cable

#### Images





#### General

Cable finishing:	textile coating
Specification:	USB 2.0

## Interface

connector:	1 x USB 2.0 Type-A male 1 x USB 2.0 Type-C™ male
Connector 1:	1 x USB 2.0 Type-C male

## **Technical characteristics**

Data transfer rate:	480 Mbps
Maximum load:	140 W
Maximum current:	5 A
Voltage:	28 V

## **Physical characteristics**

Cable length incl. connector:	1.20 m
Conductor gauge:	28 AWG data line 20 AWG power line
Colour:	black