



## Adapter USB 2.0 Type-C<sup>™</sup> male > 1 x Serial RS-232 RJ45 male 5.0 m grey

Description

This USB 2.0 to RS-232 adapter by Delock is suitable for the console control at CISCO routers, switches, access points and other compatible devices via PC or laptop.



5 m

ltem no. 89892

EAN: 4043619898923

Country of origin: China

Package: Zip poly bag

## Connectors:

- 1 x USB 2.0 Type-C male
- 1 x Serial RS-232 RJ45 male
- Chipset: FTDI FT232RL
- Compatible with USB 3.0, USB 2.0, and USB 1.1 full speed 12 Mbps
- Data transfer rate up to 230.4 Kb/s
- · Colour: grey
- · Cable length inc. connectors: ca. 5.0 m
- Suitable for various compatible CISCO devices

## System requirements

• Windows 7/7-64/8.1/8.1-64/10/10-64/Windows Server 2012 R2/Windows Server 2016, ex

Linux Kernel 2.6, ex MAC OS 10.9

PC or laptop with a free USB Type-C port

Package content

• USB 2.0 to 1 x Serial adapter

## Images







| General   |   |
|---|---|
| Function:   | Plug & Play   |
| Specification:  | RS-232 (EIA / TIA)  |
|   | USB 1.1   |
|   | USB 2.0   |
| Supported operating system:   | Linux Kernel 2.6 or above   |
|   | Mac OS 10.9 or above  |
|   | Windows 10 32-bit   |
|   | Windows 10 64-bit   |
|   | Windows 7 32-bit  |
|   | Windows 7 64-bit  |
|   | Windows 8.1 32-bit  |
|   | Windows 8.1 64-bit  |
|   |   |
| Interface   |   |
| Interface<br>Connector 1:   | 1 x USB 2.0 Type-A male   |
|   | 1 x USB 2.0 Type-A male<br>1 x RJ45 plug  |
| Connector 1:  |   |
| Connector 1:<br>Connector 2:  |   |
| Connector 1:<br>Connector 2:<br>Technical characteristics   | 1 x RJ45 plug   |
| Connector 1:<br>Connector 2:<br>Technical characteristics<br>Chipset:   | 1 x RJ45 plug<br>FTDI FT232RL   |
| Connector 1:<br>Connector 2:<br>Technical characteristics<br>Chipset:<br>Data transfer rate:                                | 1 x RJ45 plug<br>FTDI FT232RL<br>up to 230.4 Kb/s   |
| Connector 1:<br>Connector 2:<br>Technical characteristics<br>Chipset:<br>Data transfer rate:                                | 1 x RJ45 plug<br>FTDI FT232RL<br>up to 230.4 Kb/s<br>128 byte                             |
| Connector 1:<br>Connector 2:<br>Technical characteristics<br>Chipset:<br>Data transfer rate:<br>FIFO:                       | 1 x RJ45 plug<br>FTDI FT232RL<br>up to 230.4 Kb/s<br>128 byte<br>256 Byte                 |
| Connector 1:<br>Connector 2:<br>Technical characteristics<br>Chipset:<br>Data transfer rate:<br>FIFO:                       | 1 x RJ45 plug<br>FTDI FT232RL<br>up to 230.4 Kb/s<br>128 byte<br>256 Byte<br>asynchronous |
| Connector 1:<br>Connector 2:<br>Technical characteristics<br>Chipset:<br>Data transfer rate:<br>FIFO:<br>Data transmission: | 1 x RJ45 plug<br>FTDI FT232RL<br>up to 230.4 Kb/s<br>128 byte<br>256 Byte<br>asynchronous |