



# Delock 16 port SATA PCI Express x4 Card

Description

The PCI Express card by Delock expands a PC by **16** internal SATA ports. Different devices such as SSDs, hard drives, DVD-drives etc. can be connected to the card.



ltem no. 90073

EAN: 4043619900732

Country of origin: China

Package: Retail Box

# Specification

- Connectors:
- 16 x SATA 6 Gb/s 7 pin plug 1 x PCI Express x4, V3.0 16 x 2 pin pin header for LED 1 x 2 pin pin header for fan (12 V)
- Chipset: Asmedia ASM1064, ASM2806
- Supports Native Command Queuing (NCQ)
- Supports S.M.A.R.T.
- Supports TRIM
- Supports DevSleep
- Bootable (CN1 CN6)

#### System requirements

- Linux Kernel 5.8 or above
- Windows 8.1/8.1-64/10/10-64
- Windows Server 2019
- PC with one free PCI Express slot

## Package content

- PCI Express card
- User manual

## Images







© 2022 by Delock. All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.





General	
Function:	bootable
	TRIM
	S.M.A.R.T.
Supported operating system:	Linux Kernel 5.8.0 or above
	Windows 10 32-bit
	Windows 10 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows Server 2019
Interface	
Connector 1:	16 x SATA 6 Gb/s 7 pin plug
Connector 2:	1 x PCI Express x4, V3.0
connector 3:	16 x 2 pin pin header for LED
connector 4:	1 x 2 pin pin header for fan (12 V)
Technical characteristics	
Chipset:	Asmedia ASM1064
	Asmedia ASM2806