



Delock PCI Express x4 Card to 2 x external SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-CTM female

Description

This PCI Express card by Delock expands the PC by two external USB 3.1 ports. Different USB devices, such as docking stations, card readers, external enclosures etc., can be connected to the card. The card allows a data transfer rate of **10 Gbps** on both ports when used simultaneously.



Specification

Connectors:

external:

2 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female internal:

- 1 x SATA 15 pin power connector
- 1 x PCI Express x4, V3.0
- Chipset: Asmedia ASM3142
- · Data transfer rate up to:

SuperSpeed USB 10 Gbps,

SuperSpeed USB 5 Gbps,

Hi-Speed 480 Mbps,

Full-Speed 12 Mbps,

Low-Speed 1.5 Mbps

- Downwards compatible to USB 3.0, USB 2.0, USB 1.1
- Power supply via SATA power connector
- Electrical power per port: max. 15 watt (5 V / 3 A)
- Supports eXtensible Host Controller Interface (xHCI) specification 1.1
- Supports Multiple INs

System requirements

- Linux Kernel 4.6.4 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC with one free PCI Express x4 / x8 / x16 / x32 slot

Package content

- PCI Express card SuperSpeed USB 10 Gbps
- · Low profile bracket
- Driver CD
- User manual

Item no. 90397

EAN: 4043619903979

Country of origin: China

Package: Retail Box







Images













General	
Form factor:	Low Profile
Supported operating system:	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	Linux Kernel 4.6.4 or above
Interface	
External:	1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-C™ female
Internal:	1 x PCI Express x4, V3.0
	1 x SATA 15 pin power connector
Technical characteristics	
Chipset:	Asmedia ASM3142
Data transfer rate:	10 Gbps