DELOCK®
we move the world

Delock SATA 3.5″ Card Reader for CFast

Description

This Card Reader can be installed into a 3.5″ bay of a PC and will be connected to a free SATA port of the motherboard. The CFast card works as additional memory as well as a hard drive for an operating system which is also bootable.

Specification

• Connector:
 external:
  1 x CFast slot
 internal:
  1 x SATA 7 pin male
  1 x SATA 15 pin male
• Push to push CFast socket
• Bootable
• Supports CFast type I / II memory cards
• Supports CFast 1.0 and 2.0
• For installation into an available 3.5″ bay
• OS independent, no driver installation necessary

System requirements

• PC with one free 3.5″ bay
• A free SATA port
• SATA connecting cable
• Power supply with a free SATA power connector

Package content

• Card Reader SATA to CFast
• Screws
• User manual

Item no. 91496

EAN: 4043619914968

Country of origin: Taiwan, Republic of China

Package: • Retail Box

Card Reader

Images

General	
Form factor:	3.5"
Supported operating system:	OS independent, no driver installation necessary
Slot:	Push to push
Supported memory card:	CFast 1.0 and 2.0
	CFast type I / II
Interface	
External:	1 x CFast Slot
Internal:	1 x SATA 15 pin male
	1 x SATA 6 Gb/s 7 pin plug