


Delock USB 2.0 Camera Module 5.04 megapixel lens side facing 55° V5 fix focus

Description

The USB 2.0 camera module by Delock offers in compact construction low power consumption as well as high resolution. It is ideally suited for installation in industrial components like IPCs, embedded systems, sensors, notebooks, smartphones, tablets and equipment construction. The use of a photosensitive sensor with back side illumination (BSI) expands the scope of this module.



Specification

- Connector: USB 2.0 5 pin jack SMT, 1 mm pitch
- Resolution: 5.04 megapixel
- With optical IR filter
- Supported formats:
 - MJPEG (compressed)
 - YUYV: YUV 4:2:2
- Maximum resolution: QSXGA (2592 x 1944)
- Automatic image control functions including
 - Automatic exposure control (AEC)
 - Automatic white balance (AWB)
 - Automatic band filter (ABF)
 - Automatic black-level calibration (ABLC)
- Image quality controls including colour saturation, gamma, sharpness (edge enhancement), lens correction, white pixel canceling, noise canceling, and automatic 50/60 Hz luminance detection
- Supports scaling
- Power consumption:
 - Sensor suspend: 90 mA
 - Sensor active: 140 mA ± 5 mA @ 640 x 480 pixel
- Operating voltage: 5 V DC
- Operating temperature: 5 °C ~ 50 °C
- Relative humidity during operation: max. 80 %
- Sensor size: 1/4 inch
- Sensitivity: 0.6 V (lx s)
- Signal to noise ratio: 36 dB
- Dynamic range: 68 dB
- Fix focus: 0.3 m ~ infinite
- Lens: F/3.0
- Frame rates:
 - 30 fps @ HVGA, VGA, XGA, 720p, QVGA
 - 15 fps @ UXGA, 1080p, QXGA
 - 7 fps @ 2592 x 1944
- Dimensions (LxWxH): ca. 62.8 x 8.0 x 12.0 mm

System requirements

- PC with UVC support
- Windows 7 / 7-64 / 8.1 / 8.1-64 / 10 / 10-64
- DirectX 9.0c and above
- Linux 2.6.15 and above with Video4Linux
- Minimum CPU P4 1.4 GHz, 512 MB RAM

Item no. 96383

EAN: 4043619963836

Country of origin: China

Package:



Package content

- Camera module
- CD-ROM with user manual

Images



General

Supported operating system:	Linux Kernel 2.6.15
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8 32-bit
	Windows 8 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
Operating system requirement:	Windows DirectX from 9.0c
	Linux with Video4Linux

Interface

connector:	USB 2.0
------------	---------

Technical characteristics

Operating voltage:	5 V
Operating temperature:	5 °C ~ 50 °C
Maximum screen resolution:	2592 x 1944 @ 7 fps
Minimum screen resolution:	160 x 144 @ 30 fps
Sensor Size:	1/4"
Current consumption:	140 mA @ 640 x 480

Physical characteristics

Length:	62.8 mm
Width:	8 mm
Height:	10 mm