

## Electronic type (Twist-lock Type) Photo Control


### Model: LC-10DT

PLACE OF ORIGIN: CHINA

MANUFACTURER: CQC

QUALITY SYSTEM: ISO9001, accredited by TUV  
Rheinland Berlin/Brandenburg Germany

ANSI C136.10 and UL773 Dual Standard Compliant  
Multi-volts design:120-277VAC (105-305VAC)



#### SPECIFICATIONS AND CHARACTERISTICS:

- UL Listed. Reference No.: E178670
- ANSI C136.10 & UL773 Standard
- Volts & Cover Color - 50/60Hz
- Gray standard for 120VAC
- Maroon standard for 240VAC
- Blue standard for 120-277VAC (105-305VAC)
- Load Rated:

LC-10DT1	120	50/60	8 A, 960W tungsten 9.8 A, 1100VA Ballast (HID)
LC-10DT2	240	50/60	8 A, 1920 VA Ballast (HID)
LC-10DT3 120-277VAC (105-305VAC)	120	50/60	8A, 960W tungsten 9.8 A, 1100VA Ballast (HID)
	208	50/60	8 A, 1660VA Ballast (HID)
	240	50/60	8 A, 1920VA Ballast (HID)
	277	50/60	2.4 A, 660 VA Ballast (HID)

- Turn-On Light Level: 10 Lux or at customer' s request
- Turn-Off Light Level: 30Lux or at customer' s request
- Optional Range of Turn On to Turn Off Ratio: 1:3
- Turn-On/Off Time Delay: <15s
- Operating Temperature: -40°C to +70°C
- MOV Surge Protection: 320J
- Energy Consumption: Less than 1Watt (120V<0.5W)
- Electrical Life: 5,000 operations at ANSI specified load test levels
- Housing: UV stabilized impact resistant polycarbonate (PC)
- Failure Mode: Fail OFF (standard)
- Size: 74mm/80mm