



OVERHANG LADDER

> This ladder may only be used in the positions as shown

STAIRWELL SCAFFOLD

STORAGE


- above.Due care and attention should be paid at all times when

- Due care and attention should be paid at all times when using the ladder.
   Always check the stability of the ladder by ensuring that it is placed on level and solid ground.
   Always check that all hinges are in the correct positions for your particular use.
   The platform may only be used when the ladder is in one of the horizontal positions.
   Set at proper (75.5 degree) angle in straight position.

### IMPORTANT: Stabilizers must be fitted before use

#### **Assembly Instructions**

- 1. Place the stabilizer bar into the end of the side rails (see
- diagram).
  2. Secure the stabilizer bar with the nut and bolt.



## Care & Maintenance

- The hinges should be lubricated with a good quality lubricant to ensure mobility.
   The hinges should be cleaned after use especially when the hinges have been subjected to dust or dirt.

Important: This ladder should never be used if any part is missing, damaged or worn.

Following the above instructions will help to maintain your appliance and ensure its maximum lifespan.

# **Multi-Purpose Ladder**

## Safety Instructions


- > To ensure your safety please read this instruction manual carefully.
- > This manual should kept for future reference.



**EN131** 

### Hinges

- 1. To unlock the hinges simply move the handle to the "o" unlock position (see diagram) and then fold the ladder section inward.
  2. The hinges will automatically lock into position once the ladder is unfolded.
  3. Always check that all hinges are securely locked into position before using the ladder.
  4. Each pair of hinges must be locked simultaneously.
  5. It is extremely dangerous to attempt to alter the positioning of the ladder, hinges or operating joints while the ladder is in use.
  6. Always keep the joints clean and free from all foreign materials, it is advisable to cover the joints during exceptionally messy jobs.



## CAUTION

To open the ladder section: Place the locking pin (black) to the "O" position. The hinge is locked when in the "L" position.



