

anony

186 St Helens Ave
Toronto, Ontario
M6H 4A1
+1 416 994 9617
sales@anony.ca




Photo: GLS-120-BAL-03

Glass 120. Chandelier

Glass 120 is as simply named as it is designed. A 120 millimeter diameter, acid etched, glass globe provides a warm, even glow. The simplicity of this light fixture makes its application versatile. Glass 120 works beautifully as a singular pendant or as a customized clustered arrangement.

Item Code

GLS-120	BAL	03	
Model	Finish	Chandelier	Temperature

Model GLS-120 Glass 120	Pendant Dimension Ø4.75 Ø120mm	Canopy Dimension Ø8in X H1.25in Ø200mm X H32mm	Dimming A. ELV B. 0-10V Extra	Lamp Life 15K hours
Finish BAL Brushed Aluminum BBR Brushed Brass	Material Aluminum Glass	Weight 5.5lbs 2.5kg	Driver Integral in Canopy	Input Voltage 120V 50/60Hz
Canopy Finish MWH Matte White	Mounting J-Box	Temperature 2200K 2700K 3000K 3500K	Lamping 90CRI 5.4W 660lm	Output Voltage 12V
Type 03 Chandelier				Certification CE Compliant Damp Rated 

Standard cable length 10'
additional extra

anony

186 St Helens Ave
Toronto, Ontario
M6H 4A1
+1 416 994 9617
sales@anony.ca



Photo: GLS-120-BBR-03

Glass 120. Chandelier

Glass 120 is as simply named as it is designed. A 120 millimeter diameter, acid etched, glass globe provides a warm, even glow. The simplicity of this light fixture makes its application versatile. Glass 120 works beautifully as a singular pendant or as a customized clustered arrangement.

Item Code

GLS-120	BBR	03	
Model	Finish	Chandelier	Temperature

Model GLS-120 Glass 120	Pendant Dimension Ø4.75 Ø120mm	Canopy Dimension Ø8in X H1.25in Ø200mm X H32mm	Dimming A. ELV B. 0-10V Extra	Lamp Life 15K hours
Finish BAL Brushed Aluminum BBR Brushed Brass	Material Aluminum Glass	Weight 5.5lbs 2.5kg	Driver Integral in Canopy	Input Voltage 120V 50/60Hz
Canopy Finish MWH Matte White	Mounting J-Box	Temperature 2200K 2700K 3000K 3500K	Lamping 90CRI 5.4W 660lm	Output Voltage 12V
Type 03 Chandelier				Certification CE Compliant Damp Rated

Standard cable length 10'
additional extra



anony

186 St Helens Ave
Toronto, Ontario
M6H 4A1
+1 416 994 9617
sales@anony.ca



Photo: GLS-120-BAL-05

Glass 120. Chandelier

Glass 120 is as simply named as it is designed. A 120 millimeter diameter, acid etched, glass globe provides a warm, even glow. The simplicity of this light fixture makes its application versatile. Glass 120 works beautifully as a singular pendant or as a customized clustered arrangement.

Item Code

GLS-120	BAL	05	
Model	Finish	Chandelier	Temperature

Model GLS-120 Glass 120	Pendant Dimension Ø4.75 Ø120mm	Canopy Dimension Ø10in X H1.25in Ø250mm X H32mm	Dimming A. ELV B. 0-10V Extra	Lamp Life 15K hours
Finish BAL Brushed Aluminum BBR Brushed Brass	Material Aluminum Glass	Weight 8.5lbs 3.85kg	Driver Integral in Canopy	Input Voltage 120V 50/60Hz
Canopy Finish MWH Matte White	Mounting J-Box	Temperature 2200K 2700K 3000K 3500K	Lamping 90CRI 9W 1100lm	Output Voltage 12V
Type 05 Chandelier				Certification CE Compliant Damp Rated

Standard cable length 10'
additional extra



anony

186 St Helens Ave
Toronto, Ontario
M6H 4A1
+1 416 994 9617
sales@anony.ca



Photo: GLS-120-BBR-05

Glass 120. Chandelier

Glass 120 is as simply named as it is designed. A 120 millimeter diameter, acid etched, glass globe provides a warm, even glow. The simplicity of this light fixture makes its application versatile. Glass 120 works beautifully as a singular pendant or as a customized clustered arrangement.

Item Code

GLS-120	BBR	05	
Model	Finish	Chandelier	Temperature

Model

GLS-120 Glass 120

Finish

BAL Brushed Aluminum
BBR Brushed Brass

Canopy Finish

MWH Matte White

Type

05 Chandelier

Standard cable length 10'
additional extra

Pendant Dimension

Ø4.75
Ø120mm

Material

Aluminum
Glass

Mounting

J-Box

Canopy Dimension

Ø10in X H1.25in
Ø250mm X H32mm

Weight

8.5lbs
3.85kg

Temperature

2200K
2700K
3000K
3500K

Dimming

A. ELV
B. 0-10V Extra

Driver

Integral in Canopy

Lamping

90CRI
9W
1100lm

Lamp Life

15K hours

Input Voltage

120V 50/60Hz

Output Voltage

12V

Certification

CE Compliant
Damp Rated



anony

186 St Helens Ave
 Toronto, Ontario
 M6H 4A1
 +1 416 994 9617
 sales@anony.ca




Photo: GLS-120-BAL-07

Glass 120. Chandelier

Glass 120 is as simply named as it is designed. A 120 millimeter diameter, acid etched, glass globe provides a warm, even glow. The simplicity of this light fixture makes its application versatile. Glass 120 works beautifully as a singular pendant or as a customized clustered arrangement.

Item Code

GLS-120	BAL		
Model	Finish	Chandelier	Temperature

Model GLS-120 Glass 120	Pendant Dimension Ø4.75 Ø120mm	Canopy Dimension Ø12in X H1.25in Ø300mm X H32mm	Dimming A. ELV B. 0-10V Extra	Input Voltage 120V 50/60Hz
Finish BAL Brushed Aluminum BBR Brushed Brass	Material Aluminum Glass	Weight 12lbs 5.4kg	Driver Integral in Canopy	Output Voltage 12V
Canopy Finish MWH Matte White	Mounting J-Box	Temperature 2200K 2700K 3000K 3500K	Lamping 90CRI 12.6W 1540lm	Certification CE Compliant Damp Rated 
Type 07 Chandelier 13 Chandelier 19 Chandelier 31 Chandelier 37 Chandelier			Lamp Life 15K hours	Standard cable length 10' additional extra

anony

186 St Helens Ave
Toronto, Ontario
M6H 4A1
+1 416 994 9617
sales@anony.ca



Photo: GLS-120-BBR-07

Glass 120. Chandelier

Glass 120 is as simply named as it is designed. A 120 millimeter diameter, acid etched, glass globe provides a warm, even glow. The simplicity of this light fixture makes its application versatile. Glass 120 works beautifully as a singular pendant or as a customized clustered arrangement.

Item Code

GLS-120	BBR		
Model	Finish	Chandelier	Temperature

Model
GLS-120 Glass 120

Finish
BAL Brushed Aluminum
BBR Brushed Brass

Canopy Finish
MWH Matte White

Type
07 Chandelier
13 Chandelier
19 Chandelier
31 Chandelier
37 Chandelier

Pendant Dimension
Ø4.75
Ø120mm

Material
Aluminum
Glass

Mounting
J-Box

Canopy Dimension
Ø12in X H1.25in
Ø300mm X H32mm

Weight
12lbs
5.4kg

Temperature
2200K
2700K
3000K
3500K

Dimming
A. ELV
B. 0-10V Extra

Driver
Integral in Canopy

Lamping
90CRI
12.6W
1540lm

Lamp Life
15K hours

Input Voltage
120V 50/60Hz

Output Voltage
12V

Certification
CE Compliant
Damp Rated



Standard cable
length 10'
additional extra