anony 186 St Helens Ave Toronto, Ontario M6H 4A1 +1 416 994 9617 sales@anony.ca



## **GLASS 120. Chandelier**

Glass 120 is as simply named as it is designed. A 120 millimeter diameter, acid etched, glass globe provides a warm, even glow. The simplicity of this light fixture makes its application versatile. Glass 120 works beautifully as a singular pendant or as a customized clustered arrangement.

# Item Code

GLS-120	BAL	03R	
Model	Finish	Chandelier	Temperature

Model GLS-120 Glass 120

**Finish** BAL Brushed Aluminum

BBR Brushed Brass

**Chandelier** 03R Chandelier

Canopy Finish MWH Matte White

Standard cable length 10' additional extra

**Pendant Dimension** Ø4.75in Ø120mm

**Material** Aluminum Steel Glass

**Mounting** J-Box, Deep min. H2.125in **Canopy Dimension** Ø4.5in X H0.25in Ø115mm X H6mm

**Weight** 3lbs 1.4kg

## Temperature 2200K

2700K 3000K 3500K **Dimming** A. ELV B. 0-10V Extra

**Driver** Integral in J-Box

Lamping 90CRI 5.4W 660Im Lamp Life 15K hours

Input Voltage

120V 50/60Hz Output Voltage

12V Certification CE Compliant

Damp Rated

anony 186 St Helens Ave Toronto, Ontario M6H 4A1 +1 416 994 9617 sales@anony.ca



# **GLASS 120. Chandelier**

Photo: GLS-120-BBR-03R

Glass 120 is as simply named as it is designed. A 120 millimeter diameter, acid etched, glass globe provides a warm, even glow. The simplicity of this light fixture makes its application versatile. Glass 120 works beautifully as a singular pendant or as a customized clustered arrangement.

Item Code

GLS-120	BBR	03R			
Model	Finish	Chandelier	Temperature +	Canopy	
Model	01100		ndant Dimension	Canopy Dimension	Dimming
GLS-120	Glass 120		.75in 20mm	Ø4.5in X H0.25in Ø115mm X H6mm	A. ELV B. 0-10V Extra
Finish		212		2.101.117.1101.111	Die fet Exile
BAL	Brushed Aluminun	n <b>Ma</b>	terial	Weight	Driver
BBR	Brushed Brass	Alu	minum	3lbs	Integral in J-Box
		Ste	el	1.4kg	-
Chandelie	er	Gla	SS	-	Lamping
03R	Chandelier			Temperature	90CRI
		Mo	unting	2200K	5.4W
Canopy F	inish	J-E	Box, Deep	2700K	660Im
MWH	Matte White	mir	n. H2.125in	3000K	
SBK	Sandtex Black			3500K	

@ 2024, anony. All rights reserved. For more information & replacement lamps email sales@anony.ca

ngth 10 ard cable le additional extra

Lamp Life 15K hours

Input Voltage 120V 50/60Hz

**Output Voltage** 12V

Certification CE Compliant Damp Rated

C Intertek





Photo: GLS-120-BAL-07R

Glass 120 is as simply named as it is designed. A 120 millimeter diameter, acid etched, glass globe provides a warm, even glow. The simplicity of this light fixture makes its application versatile. Glass 120 works beautifully as a singular pendant or as a customized clustered arrangement.

# Item Code

GLS-120	BAL	07R	
Model	Finish	Chandelier	Temperature

Model

GLS-120 Glass 120

FinishBALBrushed AluminumBBRBrushed Brass

Canopy Finish MWH Matte White

**Chandelier** 07R Chandelier

Standard cable length 10' additional extra

**Pendant Dimension** Ø4.75in Ø120mm

**Material** Aluminum Steel Glass

**Mounting** J-Box **Canopy Dimension** Ø8in X H1.25in Ø200mm X H32mm

**Weight** 9.5lbs 4.3kg

## Temperature 2200K

2700K 3000K 3500K **Dimming** A. ELV B. 0-10V Extra

**Driver** Integral in Canopy

**Lamping** 90CRI 12.6W 1540Im Lamp Life 15K hours

Input Voltage 120V 50/60Hz

Output Voltage

Certification CE Compliant Damp Rated



Glass 120 is as simply named as it is designed. A 120 millimeter diameter, acid etched, glass globe provides a warm, even glow. The simplicity of this light fixture makes its application versatile. Glass 120 works beautifully as a singular pendant or as a customized clustered arrangement.

## Item Code

GLS-120	BBR	07R	
Model	Finish	Chandelier	Temperature

Model GLS-120 Glass 120

GL3-120 G1855 120

FinishBALBrushed AluminumBBRBrushed Brass

Canopy Finish MWH Matte White

**Chandelier** 07R Chandelier

Standard cable length 10' additional extra

**Pendant Dimension** Ø4.75in Ø120mm

**Material** Aluminum Steel Glass

**Mounting** J-Box **Canopy Dimension** Ø8in X H1.25in Ø200mm X H32mm

**Weight** 9.5lbs 4.3kg

## Temperature 2200K

2700K 3000K 3500K **Dimming** A. ELV B. 0-10V Extra

**Driver** Integral in Canopy

**Lamping** 90CRI 12.6W 1540Im Lamp Life 15K hours

Input Voltage 120V 50/60Hz

**Output Voltage** 12V

Certification CE Compliant Damp Rated

Intertek





Photo: GLS-120-BAL-19R

Glass 120 is as simply named as it is designed. A 120 millimeter diameter, acid etched, glass globe provides a warm, even glow. The simplicity of this light fixture makes its application versatile. Glass 120 works beautifully as a singular pendant or as a customized clustered arrangement.

# Item Code

GLS-120	BAL	19R	
Model	Finish	Chandelier	Temperature

Model GLS-120 Glass 120

Finish

BAL Brushed Aluminum BBR Brushed Brass

Canopy Finish MWH Matte White

**Chandelier** 19R Chandelier

Standard cable length 10' additional extra

**Pendant Dimension** Ø4.75in Ø120mm

**Material** Aluminum Steel Glass

**Mounting** J-Box **Canopy Dimension** Ø12in X H1.25in Ø300mm X H32mm

**Weight** 25lbs 11.3kg

## Temperature 2200K

2700K 3000K 3500K **Dimming** A. MLV B. ELV C. 0-10V Extra

**Driver** A. Remote B. Integral in Canopy C. Integral in Canopy

**Lamping** 90CRI 34.2W 4180Im Lamp Life 15K hours

Input Voltage 120V 50/60Hz

**Output Voltage** 12V

Certification CE Compliant Damp Rated



anony

Photo: GLS-120-BBR-1

Glass 120 is as simply named as it is designed. A 120 millimeter diameter, acid etched, glass globe provides a warm, even glow. The simplicity of this light fixture makes its application versatile. Glass 120 works beautifully as a singular pendant or as a customized clustered arrangement.

# Item Code

GLS-120	BBR	19R	
Model	Finish	Chandelier	Temperature

Model GLS-120 Glass 120

Finish

BALBrushed AluminumBBRBrushed Brass

Canopy Finish MWH Matte White

**Chandelier** 19R Chandelier

Standard cable length 10' additional extra

**Pendant Dimension** Ø4.75in Ø120mm

**Material** Aluminum Steel Glass

**Mounting** J-Box **Canopy Dimension** Ø12in X H1.25in Ø300mm X H32mm

**Weight** 25lbs 11.3kg

# Temperature

2200K 2700K 3000K 3500K Dimming A. MLV B. ELV C. 0-10V Extra Driver A. Remote B. Integral in Canopy C. Integral in Canopy

**Lamping** 90CRI 34.2W 4180lm Lamp Life 15K hours

Input Voltage 120V 50/60Hz

**Output Voltage** 12V

Certification CE Compliant Damp Rated