



Photo: PHS-BABR-01

Phase. Chandelier

Inspired by the exquisite balancing act found in hanging kinetic mobiles, Phase light is an interpretation of a circle in three forms: a sphere, a disc, and a melted semi-circle. This vertical fixture is built from the bottom up to stay balanced. Every component of each tier is hand finished and weighted precisely before being attached to the arm. Each tier acts as a predictably weighted foundation for the tier above, where the process repeats. Phase conceals its wires inside the arms while maintaining perfect parallel line structures. Rather than relying on adjustable parts—which shift over time and alter the geometry of the fixture—Phase achieves a fixed equilibrium with weight and steel piping.

Item Code

PHS		01	
Model	Finish	Chandelier	Temperature


Model		Dimension		Canopy Dimension		Dimming		Lamp Life	
PHS	Phase	W38.25in W972mm		Ø5in Ø130		A. ELV B. 0-10V		15K hours	
Finish		Material		Weight		Driver		Input Voltage	
BBR	Brushed Brass	Steel		7lbs		Integral in Canopy		120V 50/60Hz	
BBZ	Brushed Antique Brass	Aluminum		6.8kg					
OBK	Black Oxide	Plexiglass							
CUS	Custom	Glass							
Chandelier		Mounting		Temperature		Lamping		Output Voltage	
01	Chandelier	J-Box		2200K 2700K 3000K 3500K		90CRI 1.8W 220lm		12V	
								Certification	
								CE Compliant Damp Rated	
									



Photo: PHS-BBR-01

Phase. Chandelier

Inspired by the exquisite balancing act found in hanging kinetic mobiles, Phase light is an interpretation of a circle in three forms: a sphere, a disc, and a melted semi-circle. This vertical fixture is built from the bottom up to stay balanced. Every component of each tier is hand finished and weighted precisely before being attached to the arm. Each tier acts as a predictably weighted foundation for the tier above, where the process repeats. Phase conceals its wires inside the arms while maintaining perfect parallel line structures. Rather than relying on adjustable parts—which shift over time and alter the geometry of the fixture—Phase achieves a fixed equilibrium with weight and steel piping.

Item Code

PHS			01
Model	Finish	Chandelier	Temperature


Model PHS Phase		Dimension W38.25in W972mm	Canopy Dimension Ø5in Ø130	Dimming A. ELV B. 0-10V	Lamp Life 15K hours
Finish BBR Brushed Brass BBZ Brushed Antique Brass OBK Black Oxide CUS Custom		Material Steel Aluminum Plexiglass Glass	Weight 7lbs 6.8kg	Driver Integral in Canopy	Input Voltage 120V 50/60Hz
Chandelier 01 Chandelier		Mounting J-Box	Temperature 2200K 2700K 3000K 3500K	Lamping 90CRI 1.8W 220lm	Output Voltage 12V
					Certification CE Compliant Damp Rated 



Photo: PHS-OBK-01

Phase. Chandelier

Inspired by the exquisite balancing act found in hanging kinetic mobiles, Phase light is an interpretation of a circle in three forms: a sphere, a disc, and a melted semi-circle. This vertical fixture is built from the bottom up to stay balanced. Every component of each tier is hand finished and weighted precisely before being attached to the arm. Each tier acts as a predictably weighted foundation for the tier above, where the process repeats. Phase conceals its wires inside the arms while maintaining perfect parallel line structures. Rather than relying on adjustable parts—which shift over time and alter the geometry of the fixture—Phase achieves a fixed equilibrium with weight and steel piping.

Item Code

PHS			01
Model	Finish	Chandelier	Temperature

Model		Dimension		Canopy Dimension		Dimming		Lamp Life	
PHS	Phase	W38.25in W972mm		Ø5in Ø130		A. ELV B. 0-10V		15K hours	
Finish		Material		Weight		Driver		Input Voltage	
BBR	Brushed Brass	Steel		7lbs		Integral in Canopy		120V 50/60Hz	
BBZ	Brushed Antique Brass	Aluminum		6.8kg					
OBK	Black Oxide	Plexiglass							
CUS	Custom	Glass							
Chandelier		Mounting		Temperature		Lamping		Output Voltage	
01	Chandelier	J-Box		2200K 2700K 3000K 3500K		90CRI 1.8W 220lm		12V	
								Certification	
								CE Compliant Damp Rated	
								