

anony

186 St Helens Ave
 Toronto, Ontario
 M6H 4A1
 +1 416 994 9617
 sales@anony.ca




Photo: PHS-BABR-01

Phase. Chandelier

Inspired by the exquisite balancing act found in hanging kinetic mobiles, Phase light is an interpretation of a circle in three forms: a sphere, a disc, and a melted semi-circle. This vertical fixture is built from the bottom up to stay balanced. Every component of each tier is hand finished and weighted precisely before being attached to the arm. Each tier acts as a predictably weighted foundation for the tier above, where the process repeats. Phase conceals its wires inside the arms while maintaining perfect parallel line structures. Rather than relying on adjustable parts—which shift over time and alter the geometry of the fixture—Phase achieves a fixed equilibrium with weight and steel piping.

Item Code

PHS		01	
Model	Finish	Chandelier	Temperature

Model PHS	Phase	Dimension W38.25in W972mm	Canopy Dimension Ø5in Ø130	Dimming A. ELV B. 0-10V Extra	Lamp Life 15K hours
Finish BBR BBZ OBK CUS	Brushed Brass Brushed Antique Brass Black Oxide Custom	Material Steel Aluminum Plexiglass Glass	Weight 7lbs 6.8kg	Driver Integral in Canopy	Input Voltage 120V 50/60Hz
Chandelier 01	Chandelier	Mounting J-Box	Temperature 2200K 2700K 3000K 3500K	Lamping 90CRI 1.8W 220lm	Output Voltage 12V
					Certification CE Compliant Damp Rated 

anony

186 St Helens Ave
 Toronto, Ontario
 M6H 4A1
 +1 416 994 9617
 sales@anony.ca




Photo: PHS-BBR-01

Phase. Chandelier

Inspired by the exquisite balancing act found in hanging kinetic mobiles, Phase light is an interpretation of a circle in three forms: a sphere, a disc, and a melted semi-circle. This vertical fixture is built from the bottom up to stay balanced. Every component of each tier is hand finished and weighted precisely before being attached to the arm. Each tier acts as a predictably weighted foundation for the tier above, where the process repeats. Phase conceals its wires inside the arms while maintaining perfect parallel line structures. Rather than relying on adjustable parts—which shift over time and alter the geometry of the fixture—Phase achieves a fixed equilibrium with weight and steel piping.

Item Code

PHS		01	
Model	Finish	Chandelier	Temperature

Model PHS Phase	Dimension W38.25in W972mm	Canopy Dimension Ø5in Ø130	Dimming A. ELV B. 0-10V Extra	Lamp Life 15K hours
Finish BBR Brushed Brass BBZ Brushed Antique Brass OBK Black Oxide CUS Custom	Material Steel Aluminum Plexiglass Glass	Weight 7lbs 6.8kg	Driver Integral in Canopy	Input Voltage 120V 50/60Hz
Chandelier 01 Chandelier	Mounting J-Box	Temperature 2200K 2700K 3000K 3500K	Lamping 90CRI 1.8W 220lm	Output Voltage 12V
				Certification CE Compliant Damp Rated 

anony

186 St Helens Ave
 Toronto, Ontario
 M6H 4A1
 +1 416 994 9617
 sales@anony.ca



Photo: PHS-OBK-01

Phase. Chandelier

Inspired by the exquisite balancing act found in hanging kinetic mobiles, Phase light is an interpretation of a circle in three forms: a sphere, a disc, and a melted semi-circle. This vertical fixture is built from the bottom up to stay balanced. Every component of each tier is hand finished and weighted precisely before being attached to the arm. Each tier acts as a predictably weighted foundation for the tier above, where the process repeats. Phase conceals its wires inside the arms while maintaining perfect parallel line structures. Rather than relying on adjustable parts—which shift over time and alter the geometry of the fixture—Phase achieves a fixed equilibrium with weight and steel piping.

Item Code

PHS		01	
Model	Finish	Chandelier	Temperature

Model PHS	Phase	Dimension W38.25in W972mm	Canopy Dimension Ø5in Ø130	Dimming A. ELV B. 0-10V Extra	Lamp Life 15K hours
Finish BBR BBZ OBK CUS	Brushed Brass Brushed Antique Brass Black Oxide Custom	Material Steel Aluminum Plexiglass Glass	Weight 7lbs 6.8kg	Driver Integral in Canopy	Input Voltage 120V 50/60Hz
Chandelier 01	Chandelier	Mounting J-Box	Temperature 2200K 2700K 3000K 3500K	Lamping 90CRI 1.8W 220lm	Output Voltage 12V
					Certification CE Compliant Damp Rated 