# anony

Toronto, Ontario M6H 4A1 +1 416 994 9617 sales@anony.ca



Photo: PHS-BBR-03

### Phase. Chandelier

Inspired by the exquisite balancing act found in hanging kinetic mobiles. Phase light is an interpretation of a circle in three forms: a sphere, a disc, and a melted semi-circle. This vertical fixture is built from the bottom up to stay balanced. Every component of each tier is hand finished and weighted precisely before being attached to the arm. Each tier acts as a predictably weighted foundation for the tier above, where the process repeats. Phase conceals its wires inside the arms while maintaining perfect parallel line structures. Rather than relying on adjustable parts—which shift over time and alter the geometry of the fixture—Phase achieves a fixed equilibrium with weight and steel piping.

Item Co	de					
PHS		03				
Model	Finish	Chandelier	Temperature			
Model			Dimension	Canopy Dimension	Dimming	Lamp Life
PHS	Phase		Ø5ft - 6ft Ø1.5m - 1.8m	Ø8in X H1.25in Ø200mm X H32mm	A. ELV B. 0-10V Extra	15K hours
Finish						Input Voltage
BBR	<b>Brushed Brass</b>		Material	Weight	Driver	120V 50/60Hz
BBZ	Z Brushed Antique Brass		Steel	15lbs	Integral in Canopy	
OBK	BK Black Oxide		Aluminum	6.8kg		Output Voltage
CUS	Custom		Plexiglass		Lamping	12V
			Glass	Temperature	90CRI	
Chandelier			2200K	5.4W	Certification	
03	Chandelier		Mounting	2700K	660lm	CE Compliant
			J-Box	3000K		Damp Rated
Due to the length of tiers, a natural arc occurs on the longest tier				3500K		onteres of the contract of the

# anony

Toronto, Ontario M6H 4A1 +1 416 994 9617 sales@anony.ca



Photo: PHS-BABR-03

### Phase. Chandelier

Inspired by the exquisite balancing act found in hanging kinetic mobiles. Phase light is an interpretation of a circle in three forms: a sphere, a disc, and a melted semi-circle. This vertical fixture is built from the bottom up to stay balanced. Every component of each tier is hand finished and weighted precisely before being attached to the arm. Each tier acts as a predictably weighted foundation for the tier above, where the process repeats. Phase conceals its wires inside the arms while maintaining perfect parallel line structures. Rather than relying on adjustable parts—which shift over time and alter the geometry of the fixture—Phase achieves a fixed equilibrium with weight and steel piping.

### Item Code

PHS	03				
Model	Finish	Chandelier	Temperature		

<b>Model</b> PHS	Phase	<b>Dimension</b> Ø5ft - 6ft Ø1.5m - 1.8m
Finish		
BBR	Brushed Brass	Material
BBZ	Brushed Antique Brass	Steel
OBK	Black Oxide	Aluminum
CUS	Custom	Plexiglass
		Glass
Chandel	ier	
03	Chandelier	<b>Mounting</b> J-Box

Due to the length of tiers, a natural arc occurs on the longest tier

Canopy Dimension Ø8in X H1.25in Ø200mm X H32mm

ial Weight
15lbs
num 6.8kg
lass

Temperature 2200K 2700K 3000K 3500K

Dimming
A. ELV
B. 0-10V Extra
Driver
Integral in Canopy

**Lamping** 90CRI 5.4W 660Im **Lamp Life** 15K hours

Input Voltage 120V 50/60Hz

Output Voltage

Certification CE Compliant Damp Rated



# anony

Toronto, Ontario M6H 4A1 +1 416 994 9617 sales@anony.ca



Photo: PHS-OBK-03

### Phase. Chandelier

Inspired by the exquisite balancing act found in hanging kinetic mobiles. Phase light is an interpretation of a circle in three forms: a sphere, a disc, and a melted semi-circle. This vertical fixture is built from the bottom up to stay balanced. Every component of each tier is hand finished and weighted precisely before being attached to the arm. Each tier acts as a predictably weighted foundation for the tier above, where the process repeats. Phase conceals its wires inside the arms while maintaining perfect parallel line structures. Rather than relying on adjustable parts—which shift over time and alter the geometry of the fixture—Phase achieves a fixed equilibrium with weight and steel piping.

Item Co	de				
PHS	03				
Model	Finish Chandelier	Temperature			
Model		Dimension	Canopy Dimension	Dimming	Lamp Life
PHS	Phase	Ø5ft - 6ft Ø1.5m - 1.8m	Ø8in X H1.25in Ø200mm X H32mm	A. ELV B. 0-10V Extra	15K hours
Finish					Input Voltage
BBR BBZ	Brushed Brass Brushed Antique Brass	<b>Material</b> Steel	<b>Weight</b> 15lbs	<b>Driver</b> Integral in Canopy	120V 50/60Hz
OBK	Black Oxide	Aluminum	6.8kg		Output Voltag
CUS	Custom	Plexiglass Glass	Temperature	<b>Lamping</b> 90CRI	12V
Chandelier			2200K	5.4W	Certification
03	Chandelier	<b>Mounting</b> J-Box	2700K 3000K	660lm	CE Compliant Damp Rated
Due to the length of tiers, a natural arc occurs on the longest tier			3500K		