



SAFETY DATA SHEET

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name HardMaster W672 Surface Reinstatement Concrete

1.2. Relevant identified uses of the substance of mixture and uses advised against

Identified Uses Rapid set concrete
Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Meon Ltd.
Railside
Northharbour Spur
Portsmouth
PO6 3TU

+44 (0) 23 9220 0606
mail@meonuk.com

1.4. Emergency Telephone Number

Emergency telephone +44 (0) 808 118 1922

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC) No: 1272/2008

Physical hazards Not Classified
Health hazards Eye Dam. 1 - H318
Skin Sens. 1 - H317
STOT SE 3 - H335

Environmental hazards Not Classified

2.2. Label Elements

Hazard symbol



HardMaster W672 Surface Reinstatement Concrete

Signal word	Danger
Hazard statement(s)	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation.
Precautionary statement(s)	P102 - Keep out of reach of children. P280 - Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 - IF ON SKIN: Wash with plenty of water. P333+P313 - If skin irritation or rash occurs: Get medical advice/ attention. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER/ doctor. P501 - Dispose of contents/ container in accordance with national regulations.
Contains	Cement, portland, chemicals
Supplementary precautionary statement(s)	P261 Avoid breathing dust. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P362+P364 Take off contaminated clothing and wash it before reuse. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/ doctor if you feel unwell. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.
2.3. Other hazards	
Other hazards	This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.1. Substances

3.2. Mixtures

Chemical	CAS No.	EC No.	REACH	Classification	Quantity
Calcium carbonate (Substance with National workplace exposure limits.)	471-34-1	207-439-9	-	Not Classified	25 - <50 %
Cement, portland, chemicals	65997-15-1	266-043-4	-	Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335	5 - <10 %
Cement, alumina, chemicals	65997-16-2	266-045-5	-	Eye Irrit. 2 - H319	10 - <25 %
Calcium dihydroxide	1305-62-0	215-137-3	01-2119475151-45-XXXX	Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335	0.5 - <1%
Crystalline Silica	1317-95-9	-	-	STOT RE 1 - H372	0.25 - <0.5%

HardMaster W672 Surface Reinstatement Concrete

Calcium dihydroxide	1305-62-0	215-137-3	-	Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335	0.025 - <0.25%
----------------------------	-----------	-----------	---	---	-------------------

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Never give anything by mouth to an unconscious person. Place unconscious person on their side in the recovery position and ensure breathing can take place. Keep affected person under observation. Get medical attention.
Skin contact	Brush off loose particles from skin. It is important to remove the substance from the skin immediately. In the event of any sensitisation symptoms developing, ensure further exposure is avoided. Remove contamination with soap and water or recognised skin cleansing agent. Get medical attention if symptoms are severe or persist after washing
Eye contact	Rinse immediately with plenty of water. Do not rub eye. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Irritation of nose, throat and airway. Difficulty in breathing. Coughing.
Ingestion	May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation.
Skin contact	May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin.
Eye contact	Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.

HardMaster W672 Surface Reinstatement Concrete

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards None known.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Avoid inhalation of dust and vapours. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Collect spillage with a shovel and broom, or similar and reuse, if possible. Collect and place in suitable waste disposal containers and seal securely. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Neutralise with acid. Caution. May generate heat. Following dilution and neutralisation, discharge to the sewer with plenty of water may be permitted. The requirements of the local water authority must be complied with if contaminated water is flushed directly to the sewer. For waste disposal, see Section 13.

HardMaster W672 Surface Reinstatement Concrete

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions on safe handling

Usage precautions

Keep out of the reach of children. Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Keep container tightly sealed when not in use. Avoid handling which leads to dust formation. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store locked up. Store away from the following materials: Acids. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage.

Storage class

Acid-reactive storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Long-term exposure limit (8-hour TWA) WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA) WEL 4 mg/m³ respirable dust

Calcium carbonate

Long-term exposure limit (8-hour TWA) WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA) WEL 4 mg/m³ respirable dust

Cement, portland, chemicals

Long-term exposure limit (8-hour TWA) WEL 10 mg/m³ inhalable dust

Long-term exposure limit (8-hour TWA) WEL 4 mg/m³ respirable dust

Calcium dihydroxide

Long-term exposure limit (8-hour TWA) WEL 5 mg/m³ respirable dust

HardMaster W672 Surface Reinstatement Concrete

Crystalline Silica

Long-term exposure limit (8-hour TWA) WEL 0.1 mg/m³ respirable dust

Calcium dihydroxide

Long-term exposure limit (8-hour TWA) WEL 5 mg/m³

WEL = Workplace Exposure Limit

Calcium dihydroxide (CAS: 1305-62-0)

DNEL Workers - Inhalation; Long term local effects: 1 mg/m³
Workers - Inhalation; Short term local effects: 4 mg/m³
General population - Inhalation; Long term local effects: 1 mg/m³
General population - Inhalation; Short term local effects: 4 mg/m³

PNEC - Fresh water; 0.49 mg/l
- Marine water; 0.32 mg/l
- STP; 3 mg/l
- Soil; 1080 mg/kg

Lithium carbonate (CAS: 554-13-2)

DNEL Workers - Inhalation; Long term systemic effects: 10 mg/m³
Workers - Inhalation; Short term systemic effects: 30 mg/m³
Workers - Dermal; Long term systemic effects: 64.3 mg/kg/day
Workers - Dermal; Short term systemic effects: 100 mg/kg/day
General population - Inhalation; Long term systemic effects: 9.64 mg/m³
General population - Inhalation; Short term systemic effects: 28.92 mg/m³
General population - Dermal; Long term systemic effects: 64.3 mg/kg/day
General population - Dermal; Short term systemic effects: 50 mg/kg/day
General population - Oral; Long term systemic effects: 6.43 mg/kg/day
General population - Oral; Short term systemic effects: 19.23 mg/kg/day³

PNEC - Fresh water; 9 mg/l
- Marine water; 0.9 mg/l
- Intermittent release; 0.3 mg/l
- STP; 122.2 mg/l
- Sediment (Freshwater); 35.2 mg/kg
- Sediment (Marinewater); 3.52 mg/kg
- Soil; 1.76 mg/kg

Calcium dihydroxide (CAS: 1305-62-0)

DNEL Workers - Inhalation; Long term local effects: 1 mg/m³
Workers - Inhalation; Short term local effects: 4 mg/m³
General population - Inhalation; Long term local effects: 1 mg/m³
General population - Inhalation; Short term local effects: 4 mg/m³

PNEC - Fresh water; 0.49 mg/l
- Marine water; 0.32 mg/l
- STP; 3 mg/l
- Soil; 1080 mg/kg

HardMaster W672 Surface Reinstatement Concrete

Citric acid (CAS: 77-92-9)

PNEC	- Fresh water; 0.44 mg/l - Marine water; 0.044 mg/l - STP; 1000 mg/l - Sediment (Freshwater); 34.6 mg/kg - Sediment (Marinewater); 3.46 mg/kg - Soil; 33.1 mg/kg
-------------	---

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation.

Eye/face protection

Avoid contact with eyes. Large Spillages: Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.

Hand protection

Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body protection

May cause skin sensitisation or allergic reactions in sensitive individuals. Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

Respiratory protection

No specific recommendations. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn.

Environmental exposure controls

Keep container tightly sealed when not in use. Avoid release to the environment.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Cement. Powder.
Colour	Various colours.
Odour	Slight.
Odour threshold	Not determined.
pH	≥ 11.5
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	Not determined.
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Vapour pressure	Not determined.

HardMaster W672 Surface Reinstatement Concrete

Vapour density	Not determined.
Relative density	Not determined.
Bulk density	Not determined.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition temperature	Not determined.
Viscosity	Not determined.
Explosive properties	Not considered to be explosive.
Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidizing.

9.2. Other information

No information required.

SECTION 10: Stability and reactivity

10.1. Reactivity

There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stable at normal ambient temperatures and when used as recommended.
Stable under the prescribed storage conditions.

10.3. Possibility of hazardous reactions

No potentially hazardous reactions known.

10.4. Conditions to avoid

There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid: Acid anhydrides. Acids. Phenols, cresols.

10.6. Hazardous decomposition products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Skin Irrit. 2 - H315 Causes skin irritation.

Serious eye damage/irritation

Serious eye damage/irritation Eye Dam. 1 - H318 Causes serious eye damage.

Respiratory sensitisation

HardMaster W672 Surface Reinstatement Concrete

Respiratory sensitisation	Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Skin sensitisation	May cause skin sensitisation or allergic reactions in sensitive individuals.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable as to its carcinogenicity to humans.
<u>Reproductive toxicity</u>	
Reproductive toxicity – Fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - Development	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	STOT SE 3 - H335 May cause respiratory irritation.
Target organs	Respiratory system, lungs
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
<u>Aspiration hazard</u>	
Not relevant. Solid.	
General information	Dust may irritate the eyes and the respiratory system. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	A single exposure may cause the following adverse effects: Irritation of nose, throat and airway. Difficulty in breathing. Coughing.
Ingestion	May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation.
Skin contact	May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to skin.
Eye contact	Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.
Route of entry	Ingestion Inhalation Skin and/or eye contact.
Target organs	Respiratory system, lungs.
Medical considerations	Skin disorders and allergies.

HardMaster W672 Surface Reinstatement Concrete

Calcium carbonate

Acute toxicity - oral

Notes (oral LD₅₀)

> 2000 mg/kg, Rat REACH dossier information.

Acute toxicity - dermal

Notes (dermal LD₅₀)

> 2000 mg/kg, Rat REACH dossier information.

Skin corrosion/irritation

Animal data

Dose: 0.5 g, 4 hours, Rabbit Erythema/eschar score: No erythema (0). Oedema score: No oedema (0). REACH dossier information. Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation

Dose: 0.1 ml (61 mg), 72 hours, Rabbit REACH dossier information. Not irritating.

Skin sensitisation

Skin sensitisation

Local Lymph Node Assay (LLNA) - Mouse: Not sensitising. REACH dossier information.

Germ cell mutagenicity

Genotoxicity - in vitro

Chromosome aberration: Negative. REACH dossier information.

Reproductive toxicity

Reproductive toxicity - fertility

Screening - NOEL 1000 mg/kg/day, Oral, Rat P REACH dossier information. No evidence of reproductive toxicity in animal studies.

Reproductive toxicity - development

Developmental toxicity: - NOAEC: > 1.25 %, Oral, Rat REACH dossier information.

Cement, alumina, chemicals

Acute toxicity - oral

Notes (oral LD₅₀)

LD₅₀ >2000 mg/kg, Oral, Rat REACH dossier information. Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀)

LD₅₀ >2000 mg/kg, Dermal, Rat REACH dossier information. Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀)

LC₅₀ 7.6 mg/l, Inhalation, Rat REACH dossier information. Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data

Dose: 0.5 g, 4 hours, Rabbit Primary dermal irritation index: 0 REACH dossier information. Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation

Dose: 62 mg, 24 hours, Rabbit REACH dossier information. Causes serious eye irritation.

Skin sensitisation

Skin sensitisation

Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier information. Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro

Chromosome aberration: Negative. REACH dossier information. Based on available data the classification criteria are not met.

Genotoxicity - in vivo

Chromosome aberration: Negative. REACH dossier information. Based on available data the classification criteria are not met.

HardMaster W672 Surface Reinstatement Concrete

Reproductive toxicity

Reproductive toxicity - development

Embryotoxicity: Teratogenicity: - NOAEL: 266 mg/kg/day, Oral, Rat REACH dossier information. Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard

Not relevant. Solid.

Cement, portland, chemicals

Skin corrosion/irritation

Animal data

Skin Irrit. 2 - H315 Causes skin irritation.

Serious eye damage/irritation

Serious eye damage/irritation

Eye Dam. 1 - H318 Causes serious eye damage.

Skin sensitisation

Skin sensitisation

Skin Sens. 1 - H317 May cause an allergic skin reaction.

Specific target organ toxicity - single exposure

STOT - single exposure

STOT SE 3 - H335 May cause respiratory irritation.

Calcium dihydroxide

Acute toxicity - oral

Notes (oral LD₅₀)

LD₅₀ : >2000 mg/kg, Oral, Rat REACH dossier information.

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg)

2,500.0

Species

Rabbit

Notes (dermal LD₅₀)

REACH dossier information.

ATE dermal (mg/kg)

2,500.0

Skin corrosion/irritation

Animal data

Dose: 0.5 g, 4 hours, Rabbit Erythema/eschar score: Well defined erythema (2). Oedema score: Very slight oedema - barely perceptible (1). REACH dossier information. Irritating.

Serious eye damage/irritation

Serious eye damage/irritation

Causes serious eye damage.

Germ cell mutagenicity

Genotoxicity - in vitro

Chromosome aberration: Negative. REACH dossier information.

Carcinogenicity

Carcinogenicity

NOAEL 21500 mg/kg/day, Oral, Rat REACH dossier information. Read across data. No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Reproductive toxicity - development

Developmental toxicity: - NOAEL: \geq 440 mg/kg/day, Oral, Mouse REACH dossier information. Read across data. No evidence of reproductive toxicity in animal studies.

Specific target organ toxicity - single exposure

STOT - single exposure

STOT SE 3 - H335 May cause respiratory irritation.

Target organs

Respiratory system, lungs

HardMaster W672 Surface Reinstatement Concrete

Crystalline Silica

Specific target organ toxicity - repeated exposure

STOT - repeated exposure

STOT RE 1 - H372 Causes damage to organs through prolonged or repeated exposure if inhaled.

SECTION 12: Ecological information

Ecotoxicity

The product may affect the acidity (pH) of water which may have hazardous effects on aquatic organisms.

12.1. Toxicity

Toxicity

Based on available data the classification criteria are not met.

Calcium carbonate

Toxicity

Aquatic toxicity is unlikely to occur. Based on available data the classification criteria are not met.

Acute toxicity - fish

LC₅₀, 96 hours: > 100 %, Onchorhynchus mykiss (Rainbow trout)
NOEC, 96 hours: > 100 %, Onchorhynchus mykiss (Rainbow trout)
REACH dossier information.

Acute toxicity - aquatic invertebrates

EC₅₀, 48 hours: > 100 %, Daphnia magna
NOEC, 48 hours: 100 %, Daphnia magna
REACH dossier information.

Acute toxicity - aquatic plants

EC₁₀, 72 hours: > 14 mg/l, Desmodesmus subspicatus
EC₂₀, 72 hours: > 14 mg/l, Desmodesmus subspicatus
EC₅₀, 72 hours: > 14 mg/l, Desmodesmus subspicatus
NOEC, 72 hours: 14 mg/l, Desmodesmus subspicatus
REACH dossier information.

Acute toxicity - microorganisms

EC₅₀, 3 hours: > 1000 mg/l, Activated sludge
NOEC, 3 hours: 1000 mg/l, Activated sludge
REACH dossier information.

Cement, alumina, chemicals

Toxicity

Based on available data the classification criteria are not met.

Acute toxicity - fish

LC₅₀, 96 hours: >100 mg/l, Brachydanio rerio (Zebra Fish)

Acute toxicity - aquatic invertebrates

EC₅₀, 48 hours: 5.4 mg/l, Daphnia magna

Acute toxicity - aquatic plants

EC₅₀, 72 hours: 3.6 mg/l, Selenastrum capricornutum

Acute toxicity - microorganisms

EC₅₀, 3 hours: >1000 mg/l, Activated sludge

HardMaster W672 Surface Reinstatement Concrete

Cement, portland, chemicals

Toxicity Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

Calcium dihydroxide

Acute toxicity - fish LC₅₀, 96 hours: 457 mg/l, Gasterosteus aculeatus (Three-spined stickleback)
REACH dossier information.

Acute toxicity - aquatic invertebrates LC₅₀, 96 hours: 158 mg/l, Crangon septemspinosa
REACH dossier information.

Acute toxicity - aquatic plants EC₁₀, 72 hours: 79.22 mg/l, Pseudokirchneriella subcapitata
EC₂₀, 72 hours: 106.02 mg/l, Pseudokirchneriella subcapitata
EC₅₀, 72 hours: 184.57 mg/l, Pseudokirchneriella subcapitata
LOEC, 72 hours: 80 mg/l, Pseudokirchneriella subcapitata
NOEC, 72 hours: 48 mg/l, Pseudokirchneriella subcapitata
REACH dossier information.

Acute toxicity - microorganisms EC₂₀, 3 hours: 229.2 mg/l, Activated sludge
EC₅₀, 3 hours: 300.4 mg/l, Activated sludge
REACH dossier information.

Acute toxicity - terrestrial NOEC, 4 weeks: 2000 mg/kg, Eisenia Fetida (Earthworm)
REACH dossier information.

Chronic toxicity - aquatic invertebrates LC₅₀, 14 days: 53.1 mg/l, Crangon septemspinosa
NOEC, 14 days: 32 mg/l, Crangon septemspinosa
REACH dossier information.

Toxicity to soil NOEC, 96 days: 4000 mg/kg, Soil
EC₅₀, 28 days: > 12000 mg/kg, Soil
REACH dossier information.

Toxicity to terrestrial plants EC₅₀, 21 days: 5640 mg/kg, Allium porrum
REACH dossier information.

Crystalline Silica

Toxicity No negative effects on the aquatic environment are known.

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Calcium carbonate

Persistence and degradability The product contains only inorganic substances which are not biodegradable.

Cement, alumina, chemicals

Persistence and degradability The product contains only inorganic substances which are not biodegradable.

Crystalline Silica

Persistence and degradability The product contains only inorganic substances which are not biodegradable.

HardMaster W672 Surface Reinstatement Concrete

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.
Partition coefficient Not determined.

Calcium carbonate

Bioaccumulative potential No data available on bioaccumulation.

Cement, alumina, chemicals

Bioaccumulative potential No data available on bioaccumulation.
Partition coefficient Technically not feasible.

Calcium dihydroxide

Bioaccumulative potential The product is not bioaccumulating.

Crystalline Silica

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility No data available.

Calcium carbonate

Mobility The product is soluble in water.

Cement, alumina, chemicals

Mobility The product is soluble in water.

Cement, portland, chemicals

Mobility No information available.

Calcium dihydroxide

Mobility The product is soluble in water.
Surface tension 72 mN/m @ 20°C REACH dossier information.

Crystalline Silica

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Calcium carbonate

Results of PBT and vPvB assessment Substance is inorganic. Not relevant.

Cement, alumina, chemicals

Results of PBT and vPvB assessment Not relevant. Substance is inorganic.

Calcium dihydroxide

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

HardMaster W672 Surface Reinstatement Concrete

Crystalline Silica

Results of PBT and vPvB assessment Substance is inorganic. Not relevant.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

General information

The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for Air Transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2014).

General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

UN Number Not applicable.

14.2. UN proper shipping name

UN proper shipping name Not applicable.

14.3. Transport hazard class(es)

Hazard class No transport warning sign required.

14.4. Packing group

Packing group Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant No.

14.6. Special precautions for user

Special precaution Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

HardMaster W672 Surface Reinstatement Concrete

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	EH40/2005 Workplace exposure limits.
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Restrictions (Title VIII Regulation 1907/2006)	Entry number: 47

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Classification procedures according to Regulation (EC) 1272/2008	Skin Sens. 1 - H317, Eye Dam. 1 - H318: Calculation method.
Training advice	Read and follow manufacturer's recommendations.
Hazard statements in full	H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H318 - Causes serious eye damage. H319 - Causes serious eye irritation. H335 - May cause respiratory irritation. H372 - Causes damage to organs through prolonged or repeated exposure if inhaled.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.