

VIALINE F210

SOLVENT BASED ACRYLIC LINE MARKING PAINT - DECLARATION OF PERFORMANCE



Spectrum ViaLine F210 is a fast drying, high-build road marking and delineation paint that can be used for almost all line marking applications. Ideal for use on hard surfaces such as roads, car parks, distribution centres and docks. ViaLine F210 is a toluene free paint, meaning it is more environmentally friendly than other products, such as chlorinated rubber. ViaLine F210 can be applied using roller, brush or spray methods, supplied in 20kg tins and available in a choice of colours. ViaLine F210 comes packaged in the innovative EnviraPac liner system, which allows maximum usage of product, recycling of clean metal tins and most importantly considerable reduction of waste costs.

FEATURES AND BENEFITS

- Fast drying, for rapid return to service
- Toluene-free - more environmentally friendly
- High solids for excellent opacity
- EnviraPac liner to allow recycling of tin and reduce disposal costs



Traffic Blue
RAL 5017



Traffic Green
RAL 6024



Traffic Red
RAL 3020



Black




Traffic
Yellow



White



CONTACT US TO FIND OUT MORE OR BOOK A
DEMONSTRATION WITH OUR TECHNICAL EXPERTS.

 CALL FREE: 0808 118 1922

 MEONUK.COM



MEON
DELIVERING GREAT SURFACES

DECLARATION OF PERFORMANCE:

APPLICATION LIMITS		TECHNICAL DATA	
Minimum temperature	5°C	Density	1.67 grams/millilitre
Maximum temperature	45°C	Solid content	78.0%
Humidity	80%	VOC level - white	378 grams/litre
		VOC level - Yellow	418 grams/litre
		VOC level - Green	410 grams/litre

APPLICATION SYSTEM 1		
Product	Application Method	Dosage
ViaLine F210	Airless spray machine	580 g/m ²
Potters AC13 850-425 bead	Injected	102 g/m ²
Potters AC13 425-125 bead	Drop on	408 g/m ²

APPLICATION SYSTEM 2		
Product	Application Method	Dosage
ViaLine F210	Airless spray machine	400 g/m ²
Potters AC13 425-125 bead	Drop on	350 g/m ²

PERFORMANCE VALUES (relate to application system 1 only)							
Wheel passes		Day time visibility		Night time visibility		Slip resistance	
P	No. of	Qd	mcd/m ² /lx	RI	mcd/m ² /lx	S	SRV
P0	0	Q4	174	R5	307	S2	54
P1	50,000	Q2	106	R4	250	S2	53
P2	100,000	Q2	120	R4	238	S2	50
P3	200,000	Q2	115	R3	191	S2	53
P4	500,000	Q2	125	R3	161	S2	50
P5	1,000,000	Q3	142	R3	179	S1	46
P5	1,000,000	Q2		R3		S1	

MEON PERFORMANCE ASSURED

Meon Performance Assured is a system Meon have created which ensures products under the MPA programme have undergone vigorous testing to give you the assurance of quality, with the stated performance values relevant when applied in accordance to the recommended application method and dosage rate.

Meon Limited declares the product referred to in this Certificate conforms with the declared performance above, when applied by a Meon trained and approved installer.

Signed on behalf of Meon Limited by:

Russell Smallridge
Supply Chain Manager, Meon Limited

Effective Date: 03/09/2020




Meon Limited: Railside, Northarbour Spur, Portsmouth, PO6 3TU
Registered in England & Wales No; 07384073 at the above address

MEON UK

+44 (0)23 9220 0606
MAIL@MEONUK.COM
MEONUK.COM

MEON IRELAND

+353 (0)1 840 7647
INFO@MEONIRELAND.COM
MEON.IE



MEON
DELIVERING GREAT SURFACES