



# PATCHMASTER H572

## TEMPORARY POTHOLE REPAIR RED - DECLARATION OF PERFORMANCE



PatchMaster H572 is a cold-lay repair material that has been specially formulated to enable first time surface restoration. Ideal for re-instatement of utility cuts, filling and patching works such as potholes. The product is ideal where a rapid response is required for reactive maintenance works, or to enable re-opening of re-instatements to traffic without having to wait for hot-works operations. Can be used throughout the year and can be used even in damp conditions for short-term reactive works.

### FEATURES AND BENEFITS

- Solvent-free formula reduces VOC's
- Remains workable all year round for easy laying
- CE marked - meets required standards
- Can be re-opened to traffic immediately after completion
- Straightforward application with no requirement for hot works
- Increases in strength over time, after application



Red



CONTACT US TO FIND OUT MORE OR BOOK A DEMONSTRATION WITH OUR TECHNICAL EXPERTS.

CALL FREE: 0808 118 1922

MEONUK.COM



**MEON**  
DELIVERING GREAT SURFACES

## DECLARATION OF PERFORMANCE:

SGS Ltd, Notified Body No. 0120 (UKCA) & No. 1029 (CE) issued the certificate of conformity of FPC on the basis of:

1. Initial inspection of the manufacturing plant
2. Factory Production Control continuous surveillance, assessment and evaluation of FPC

PERFORMANCE (Conforming to EN 13108-1:2006/AC:2008)						Mix Code: 8888.1	
Essential Characteristic	Test Method	Seive (mm)	% pass	Seive (mm)	% Pass	Seive (mm)	% Pass
Grading of Mixture	EN 12697-2	40		10	100	1	5
		31.5		6.3	90	0.5	4
		20		4	22	0.25	
		14		2	7	0.063	3
Binder Content (%)	EN 12697-1 & 39		B <sub>min</sub> %	3.6	B <sub>act</sub> %	3.3	
Temperature (°C)	EN 12697-13		Min (°C)	80	Max (°C)	100	
Void Content in Trial Strip			V <sub>min</sub>	NR	V <sub>max</sub>	NR	
Resistance to Permanent Deformation				NR			
Dangerous Substances				NR			
Resistance to Abrasion by Studded Tyres				NR			
Additive	Type			Flux Fe2O3	Composition %		1.3 2
Water Sensitivity				NR			
Stiffness				NR			
Resistance to Fatigue				NR			
Polished Stone Value				55			

### MEON PERFORMANCE ASSURED

Meon Performance Assured is a system Meon have created which ensures products under the MPA programme have undergone vigorous testing to give you the assurance of quality, with the stated performance values relevant when applied in accordance to the recommended application method and dosage rate.

Meon Limited declares the product referred to in this Certificate conforms with the declared performance above, when applied by a Meon trained and approved installer.

Signed on behalf of Meon Limited by:

Russell Smallridge  
Supply Chain Manager, Meon Limited

Effective Date: 16/10/2020




Meon Limited: Railside, Northarbour Spur, Portsmouth, PO6 3TU  
Registered in England & Wales No; 07384073 at the above address

#### MEON UK

+44 (0)23 9220 0606  
MAIL@MEONUK.COM  
MEONUK.COM

#### MEON IRELAND

+353 (0)1 840 7647  
INFO@MEONIRELAND.COM  
MEON.IE



**MEON**  
DELIVERING GREAT SURFACES