

MULTIGRIP X440



SINGLE PACK EPOXY SLIP-RESISTANT PAINT -DECLARATION OF PERFORMANCE



MultiGrip X440 is a single-pack solvent based paint system with good slip resistance properties. It is manufactured using a tough epoxy-ester based product, for high build, stable colour retention and good wear characteristics. It contains a slip-resist particle to increase the slip resistance value, can be fully machine or hand applied, and is fast drying to minimise closures and downtime. It is ideally suited for safe walkways and has been used very successfully on airfields, ports and docks, distribution centres, car parks and retail shopping centres, to name just a few examples. MultiGrip X440 comes packaged in the innovative EnviraPac liner system, which allows maximum usage of product, recycling of clean metal tins and most importantly considerable reduction of waste costs.

FEATURES AND BENEFITS

- Good SRV
- · Can be applied on various substrates
- · Fast cure time
- · Fully sprayable; can also be roller applied
- · Large stock selection of bright and vivid colours
- · EnviraPac liner to allow recycling of tin and reduce disposal costs



Traffic Green Signal Yellow RAL6024 RAL1003













CONTACT US TO FIND OUT MORE OR BOOK A DEMONSTRATION WITH OUR TECHNICAL EXPERTS.



CALL FREE: 0808 118 1922





MDOP.039 - MultiGrip X440

DECLARATION OF PERFORMANCE:

PERFORMANCE DATA	
VOC Level (all colours)	390 grams/litre ± 5%
Flash point	4°C
Auto ignition temperature	>480°C
Relative density	1.41 - 1.55 grams/ml
Viscocity	~ 2.5 poise

SLIP RESISTANCE PERFORMANCE (To stated appl				
Air temperature		2-4°C		
SRV			Average	
No additional aggregate	Asphalt	Dry	79	
		Wet	62	
	Concrete	Dry	86	
		Wet	62	

Molochite addition @ 16% by weight Concrete Wet 62

Molochite Asphalt Wet 72

Dry 94

Wet 72

Dry 95

Wet 85

MEON PERFORMANCE ASSURED

Meon Performance Assured is a system Meon have created which ensures products under the MPA programme have undergone vigorous testing to give you the assurance of quality, with the stated performance values relevant when applied in accordance to the recommended application method and dosage rate.

Meon Limited declares the product referred to in this Certificate conforms with the declared performance above, when applied by a Meon trained and approved installer.

Signed on behalf of Meon Limited by:

Russell Smallridge Supply Chain Manager, Meon Limited

Effective Date: 09/12/2020

Julie



Meon Limited: Railside, Northarbour Spur, Portsmouth, PO6 3TU Registered in England & Wales No; 07384073 at the above address

MEON UK





MEONUK.COM

MEON IRELAND

() + 353 (0)1 840 7647

■ INFO@MEONIRELAND.COM

© MEON.IE



^{*}Variations in temperature can affect the slip resistant value