

# VIALINE F216


## HIGHWAY SPEC ACRYLIC LINE MARKING PAINT - DECLARATION OF PERFORMANCE




Spectrum ViaLine F216 is a high quality, fast drying road marking and delineation paint that is designed for use on highways, but can be used for most line marking applications such as roads, car parks and distribution centres and can also be used to refresh thermoplastic markings. ViaLine F216 is a toluene free, high solid content and low odour paint. It features high bead retention properties which ensures long term performance with high durability and retro-reflectivity. ViaLine F216 comes packaged in the innovative EnviraPac liner system, which allows maximum usage of product, recycling of clean metal tins and most importantly, considerable reduction of waste costs.

### FEATURES AND BENEFITS

- Excellent durability and retro-reflectivity - Certified to 2,000,000 wheel passes
- High solid content for excellent opacity, specifically designed for highway use
- Enhanced binder formulation for increased adhesion to substrate
- Ideal for refreshing thermoplastic lines to minimise build-up



CONTACT US TO FIND OUT MORE OR BOOK A  
DEMONSTRATION WITH OUR TECHNICAL EXPERTS.

 CALL FREE: 0808 118 1922

 MEONUK.COM



**MEON**  
DELIVERING GREAT SURFACES

**DECLARATION OF PERFORMANCE:****TECHNICAL DATA**

Colour (x)	0.32
Colour (y)	0.3364

**APPLICATION LIMITS**

Minimum air temperature	5°C
Minimum surface temperature (over dew point)	3°C
Maximum surface temperature	45°C
Maximum Humidity	75%

**APPLICATION SYSTEM**

Product	Application Method	Dosage
ViaLine F216	Spray applied	490g/m <sup>2</sup>
Echostar 5 SBP ECO SRT	Drop on	400g/m <sup>2</sup>

**PERFORMANCE VALUES**

In accordance to EN 13197:2012+A1:2014

Wheel passes		Day time visibility		Night time visibility		Slip resistance	
P	No. of	Qd	mcd/m <sup>2</sup> /lx	RL	mcd/m <sup>2</sup> /lx	S	SRV
P0	0	Q5	252	R4	225	S3	58
P2	100,000	Q5	251	R4	242	S2	53
P3	200,000	Q5	248	R4	210	S1	48
P4	500,000	Q5	239	R3	179	S1	47
P5	1,000,000	Q5	219	R2	144	S1	46
P6	2,000,000	Q4	196	R2	124	S1	46
<b>P6</b>		<b>Q4</b>		<b>R2</b>		<b>S1</b>	

**MEON PERFORMANCE ASSURED**

Meon Performance Assured is a system Meon have created which ensures products under the MPA programme have undergone vigorous testing to give you the assurance of quality, with the stated performance values relevant when applied in accordance to the recommended application method and dosage rate.

Meon Limited declares the product referred to in this Certificate conforms with the declared performance above, when applied by a Meon trained and approved installer.

Signed on behalf of Meon Limited by:

Russell Smallridge  
Supply Chain Manager, Meon Limited

Effective Date: 19/05/2021




Meon Limited: Railside, Northarbour Spur, Portsmouth, PO6 3TU  
Registered in England & Wales No; 07384073 at the above address

**MEON UK**

+44 (0)23 9220 0606  
MAIL@MEONUK.COM  
MEONUK.COM

**MEON IRELAND**

+353 (0)1 840 7647  
INFO@MEONIRELAND.COM  
MEON.IE



**MEON**  
DELIVERING GREAT SURFACES