

CONTEC ALPHA230MM FLOOR GRINDER





A small grinder with incredible performance! Powered by only 110V or 230V single phase motor, the Alpha grinder reaches the class of 3 phase machines with the weight of only 44kg. Excellent for the removal of existing line markings or floor tape.

FEATURES & BENEFITS


- · Dust free due to an integrated dust port
- · Handle bar removable and adjustable for length and height
- · Removable dust shroud
- Grinds up to the wall
- · Replaceable diamond segments
- Flexible couplings
- Various Tools



CONTACT US TO FIND OUT MORE OR BOOK A DEMONSTRATION WITH OUR TECHNICAL EXPERTS.



CALL FREE: 0808 118 1922





TECHNICAL:

 Working Width:
 230mm

 Weight:
 44kg

 Voltage:
 110V / 230V

 Current:
 19.1A / 13A

 Motor Rating:
 1.5kW / 2.0kW

 Motor Rotation Speed:
 1380rpm / 1290rpm

 Height:
 900 - 1130mm

Length: 950 - 1130mm Width: 430mm Hose Diameter: 50mm

USES:

Generally used on internal applications for the removal of existing paint lines and surfaces including floor tape before applying a painted surface. A quick pass with a Contec Line Ex Shot Blaster is recommended to remove any debris and create an ideal texture for the paint to adhere to.

- Factories and warehouses
- Internal car parks and garages
- Offices and commercial buildings

RECOMMENDATION:

Recommended vacuum is Contec CDM 3000 230 V Mobile Dust Extraction Unit with a 50mm hose.


TRAINING:

Full training packages are available from Meon. This will ensure that proper usage of the machine is undertaken. Training is available onsite or at Meon.

SERVICE:

In order to ensure the Contec Dust Extractor is at maximum working capacity it is recommended that a service is booked at least once every 12 months. This may alter dependent on usage.

MEON UK





MEONUK.COM

MEON IRELAND

() + 353 (0)1 840 7647

MEON.IE

