

GRINDLAZER HP DC1013 G

13HP DRUM SCARIFIER



The GrindLazer HP DC1013 G is a forward cut drum scarifier, and is the contractor choice for all-around scarifying jobs, including car park lines, road markings, and construction sites. This machine is perfect for MMA and thermoplastic removal as well as surface smoothing. Automatic Depth Control System (DCS) is available for a perfect removal every time. With the optional LineDriver System, its productivity is unmatched and means you can get more work done everyday without the fatigue from walking.

FEATURES AND BENEFITS

- Depth Control System available - eliminate guesswork and defects
- InstaCut technology - floating deck ideal for using on uneven surfaces
- TriBelt drive system - optimised power eliminates costly downtime
- Fat Track front swivel wheel - easy to turn with no need to 'muscle' it
- Compatible with LineDriver
- Use with LazerVac extraction system to reduce airborne silica dust



CONTACT US TO FIND OUT MORE OR BOOK A DEMONSTRATION WITH OUR TECHNICAL EXPERTS.

CALL FREE: 0808 118 1922

MEONUK.COM



MEON
DELIVERING GREAT SURFACES

KEY FEATURES:

INSTACUT TECHNOLOGY

Ultimate removal or inlay flexibility. Only unit to offer 'hands-on' engagement of the cutting deck system for up or down position. Allows deck to float when on uneven surfaces. No-tool system.

DURABLE 13 HP ENGINE WITH CYCLONE FILTER

Contractor preferred power. Cyclone filter protects the engine from harmful airborne dust.

EXTREME-DUTY PROSTART SYSTEM

Centrifugal clutch allows easy starting and shut-off of cutters, providing a safe start-up system. Easy to start in cold weather.

DEPTH CONTROL SYSTEM

Eliminate measuring and guesswork. Quickly and easily adjust the cutter depth to align with ever-changing terrain. Accurate cut depth to tape or thermoplastic inlays. Eliminates damage due to 'dropped drums'.

VACUUM PORT FOR DUST REMOVAL

Allows for linking up a LazerVac and cyclone separator vacuum system for the reduction of airborne dust. Compatible with:

- LazerVac 330 Electric
- LazerVac 550 Petrol & (optional) Cyclone 32 Separator

TECHNICAL:

NOISE LEVEL

SOUND POWER (ISO 3744):	109.3 dBa
SOUND PRESSURE:	93.6 dBa (measured at 1 metre)
VIBRATION LEVEL (ISO 5349)	
WITHOUT LINEDRIVER:	7.5m/sec ²
WITH LINEDRIVER:	5.9m/sec ²
APPROX REMOVAL RATE	
WITHOUT LINEDRIVER:	74m ² /hour
WITH LINEDRIVER:	160m ² /hour
WORKING WIDTH:	200mm
WEIGHT:	141kg
POWER RATING (SAE J1349):	11.0HP @ 3600 rpm






TRAINING:

Full training packages are available from Meon. This will ensure that proper usage of the machine is undertaken. Training is available on-site or at Meon head office.

SERVICE:

In order to ensure the Graco Graco GrindLazer HP DC1013 G is at maximum working capacity it is recommended that a service is booked at least once every 12 months. This may alter dependant on usage and materials used.

CUTTERS:

CUTTER TYPE	Wire Brush	Carbide Flail	Carbide Miller	Carbide Pick	PCD Flat
IMAGE:					
CODE:	601540	601789	601788	601873	601863
Surface Preparation:	✓	✓	✓	✓	✓
Dirt/Laitance Removal:	✓	✓			
Paint Removal:		✓		✓	
Tape Removal:			✓	✓	✓
Thermoplastic Removal:			✓	✓	✓
MMA Removal:		✓	✓	✓	✓

MEON UK

- +44 (0)23 9220 0606
- MAIL@MEONUK.COM
- MEONUK.COM

MEON IRELAND

- +353 (0)1 840 7647
- INFO@MEONIRELAND.COM
- MEON.IE



MEON
DELIVERING GREAT SURFACES