

BITUSEAL H561

COLD APPLIED FLEXIBLE JOINT TAPE



BituSeal H561 is a cold applied, self adhesive tape which provides a flexible joint between ironwork reinstatements and surrounding asphalt. The polymer modified bitumen tape offers a very simple and easy to use solution to create a flexible, watertight seal around the reinstatement which will remove the risk of failure due to substrate movement and removes the need for overbanding.

FEATURES AND BENEFITS


- Flexible joint - prevents failures around ironworks
- Creates watertight seal - no need to overband
- Cold applied - reduce hot works
- Self adhesive - easy to use



Black



CONTACT US TO FIND OUT MORE OR BOOK A DEMONSTRATION WITH OUR TECHNICAL EXPERTS.

 CALL FREE: 0808 118 1922

 MEONUK.COM



MEON
DELIVERING GREAT SURFACES

PREPARATION:

The application surface should be sound and clean, free from grease, oil, rust, scale, dirt, or any other soiling that might affect adhesion or performance. The surface should be reasonably dry, sufficient dryness can be achieved by blowing dry the surface with a leaf blower. BituSeal H561 can be used on asphalt and concrete surfaces.

APPLICATION:

The surface temperature must be over -20°C and below 80°C.

BituSeal H561 must be applied before installation of the surface course of the reinstatement. Measure the sides of the reinstatement to find out the length of BituSeal H561 required. Roll out the BituSeal H561 and cut to the required length. Remove a small part of the backing from one end of the tape and press the tape into place level with the surface of the wearing course. Continue pressing the tape into place, removing the backing at the same time. BituSeal H561 will bend at 90° into a tight corner to create a complete seal.

The wearing course can be installed as soon as BituSeal H561 is in place.

TECHNICAL:

Dimensions	45mm x 8mm x 5m	
Density	1.5g/ml	
Softening point	135°C	
Elastic recovery @ 10°C	50% (52mm extension)	EN 13398
Elastic recovery @ 25°C	60% (200mm extension)	EN 13398
Cold bend behaviour @ 0°C	No cracks	DIN 521123

STORAGE AND PACKAGING:

STORAGE CONDITIONS:

Storage area should be dry, protected from direct sunlight and extremes of temperature - i.e. between 5 & 20°C.

SHELF LIFE:

Minimum 12 months when stored under cover, in original unopened containers, in accordance with Storage Condition guidelines listed above.

HEALTH AND SAFETY:

Wear suitable protective clothing, gloves and eye/face protection. Familiarise yourself with the material safety data sheets before using this product. If you need a copy please call our technical team on **023 9220 0606**.

MEON UK

+44 (0)23 9220 0606
 MAIL@MEONUK.COM
 MEONUK.COM

MEON IRELAND

+353 (0)1 840 7647
 INFO@MEONIRELAND.COM
 MEON.IE



MEON
 DELIVERING GREAT SURFACES